

JOB NO.: TCS00881/18

CEDD CONTRACT CV/2016/10
SITE FORMATION AND ASSOCIATED INFRASTRUCTURAL
WORKS FOR DEVELOPMENT OF COLUMBARIUM AT
SANDY RIDGE CEMETERY

MONTHLY ENVIRONMENTAL MONITORING AND AUDIT REPORT (No.3) – OCTOBER 2018

PREPARED FOR

HSIN CHONG TSUN YIP JOINT VENTURE

Date Reference No. Prepared By Certified By

 $14\ November\ 2018\ TCS00881/18/600/R189v2$

Nicola Hon Tam Tak Wing (Environmental Consultant) (Environmental Team Leader)

Version	Date	Remarks
1	6 November 2018	First Submission
2	14 November 2018	Amended according to the IEC's comment 12 November 2018



Our Ref: TCS00881/18/300/L0194

Hsin Chong Tsun Yip Joint Venture

Hsin Chong Center, 107-109 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong

Attn: Mr. HO Man To

14 November 2018 By e-mail

Dear Sirs,

Re: CEDD Contract CV/2016/10

> Site Formation and Associated Infrastructural Works for Development of Columbarium at Sandy Ridge Cemetery

Monthly Environmental Monitoring & Audit Report (No.3) – October 2018

We confirmed that the captioned report has complied with the requirement set out in the EM&A Manual, we hereby certify the captioned report pursuant to Specific Condition 3.4 of the Environmental Permit No. FEP-01/534/2017 and EP-534/2017.

Should you have any queries, please feel free to contact the undersigned at Tel: 2959-6059 or Fax: 2959-6079 or Email: twtam@fordbusiness.com.

Yours sincerely, For and on Behalf of

Action-United Environmental Services & Consulting (AUES)

T. W. Tam

Environmental Team Leader

TW/nh

cc **CEDD** Mr. Joseph Wong

By-email

Arup (RE)

Mr. Steve Tang

By-email

Acuity (IEC)


Tel

Fax

Email













Our ref: CJO4068

Hsin Chong Tsun Yip Joint Venture (CV/2016/10) Hsin Chong Centre 107-109 Wai Yip Street Kwun Tong, Kowloon Hong Kong

Attention: Mr. HO Man-to

14 November 2018

Dear Sir,

Site formation and Associated Infrastructural Works for Development of Columbarium at Sandy Ridge Cemetery

Website: www.acuityhk.com

Nos. 301–305 Castle Peak Road, Kwai Chung, New Territories

Unit 1908, iPlace,

Tel.: (852) 2698 6833

Fax.: (852) 2698 9383

Monthly Environmental Monitoring and Audit Report (No.3) October 2018

I refer to the email of ETL dated 14 November 2018 regarding the captioned. We have no further comment on the Monthly Environmental Monitoring and Audit Report (No.3) October 2018 (Version 2) dated 14 November with reference No. TCS00881/18/600/R189v2 after verification.

Yours faithfully,

CH Leung

Ir Leung CH Jacky
Independent Environmental Checker

cc. CEDD-DPTL/Land Works – Mr. LI Kwok Hung
ARUP – Mr. LEE Davis
ET Leader – Mr. TAM



EXECUTIVE SUMMARY

- ES.01. Civil Engineering and Development Department (hereafter referred as "CEDD") is the Project Proponent for the Project "Site Formation and Associated Infrastructural Works for Development of Columbarium, Crematorium and Related Facilities at Sandy Ridge Cemetery" (hereafter referred as "the Project"). The Project is a Designated Project to be implemented under Environmental Permit No. EP-534/2017. To facilitate the Project management, the Project works were separated into three different Contracts and they are listed below.
 - CEDD Contract No. CV/2016/10 Site Formation and Associated Infrastructural Works for Development of Columbarium at Sandy Ridge Cemetery (hereafter referred as "Contract 1")
 - CEDD Contract No. CV/2017/02 Infrastructural Works at Man Kam To Road and Lin Ma Hang Road for Development of Columbarium at Sandy Ridge Cemetery (hereafter referred as "Contract 2")
 - Other CEDD's Contract as related Development of Columbarium at Sandy Ridge Cemetery (hereafter referred as "Contract 3")
- ES.02. Hsin Chong Tsun Yip Joint Venture (hereafter referred as "HCTYJV") has been awarded the *CEDD Contract No. CV/2016/10* "Site Formation and Associated Infrastructural Works for Development of Columbarium at Sandy Ridge Cemetery" on 5 December 2017. According to the Contract requirement, HCTYJV shall take over the responsibility for part of the Environmental Permit No. EP-534/2017 for ease of management, therefore application for Further Environmental Permit was submitted by HCTYJV to EPD on 26 January 2018 and Further Environmental Permit No. FEP-01/534/2017 was granted to HCTYJV by EPD on 23 February 2018.
- ES.03. Action-United Environmental Services & Consulting (hereinafter referred as "AUES") has been commissioned by HCTYJV as an Environmental Team (hereinafter referred as "the ET") to implement the Environmental Monitoring & Audit (EM&A) programme in accordance with the approved EM&A Manual as well as the associated duties.
- ES.04. As notified by HCTYJV, construction works of the Contract 1 was commenced on 16 August 2018 and therefore construction phase impact monitoring was started on 16 August 2018.
- ES.05. This is the 3rd monthly Environmental Monitoring and Audit Report to reporting the monitoring results and inspection findings for the period from 1 to 31 October 2018 (the Reporting Month).

ENVIRONMENTAL MONITORING AND AUDIT ACTIVITIES

ES.06. Environmental monitoring activities under the EM&A program in this Reporting Month is summarized in the following table.

Table ES-4 Environmental monitoring activities in the Reporting Period

Issues	Environmental Monitoring Parameters / Inspection	Monitoring Location under CV/2016/10	Occasions
Air Ovolity	1-hour TSP	ASR-1	15
Air Quality	24-hour TSP	ASR-1	6
Construction Noise	Leq (30min) Daytime	CN-1	4
Water Quality	In-situ measurement and Water sampling	M3	14
Ecology	Monthly Monitoring	Transect within site area of CV/2016/10	1
Landscape & Visual	Monthly Site Inspection	Site area of CV/2016/10	1
Inapaction / Audit	ET Regular Environmental Site Inspection	Site area of CV/2016/10	5
Inspection / Audit	IEC Monthly Environmental Site Audit	Site area of CV/2016/10	1



BREACH OF ACTION AND LIMIT (A/L) LEVELS

ES.07. No exceedance of air quality and construction noise monitoring was recorded in this Reporting Month. However, four (4) Limit Level exceedances were recorded in water quality monitoring. Notification of Exceedance (NOE) of water quality was issued. The statistics of environmental exceedance, NOE issued and investigation of exceedance are summarized in the following table.

Table ES-5 Breach of Action and Limit (A/L) Levels in the Reporting Period

Environmental	Manitaning	Action	Action Limit	Event & Action		
Issues	Monitoring Action Parameters Level			NOE Issued	Investigation findings	Corrective Actions
Air Ovolity	1-hour TSP	0	0	0	-	-
Air Quality	24-hour TSP	0	0	0	-	-
Construction Noise	Leq _{30min} Daytime	0	0	0	-	-
	DO	0	0	0	-	-
Water Quality	Turbidity	0	3	3	Not related to the Contract Works	NA
	SS	0	1	1	Not related to the Contract Works	NA

Note: NOE – Notification of Exceedance

ES.08. Investigation for the cause of water quality exceedances have been undertaken by ET. Investigation results revealed that water quality mitigation measures have been implemented to minimize the water quality impact arising from contract works. Such as temporary bund and de-silting trench were installed at Retaining Wall RW1 to reduce the suspended solids content in runoff. Series of sheet pile was installed at site boundary to prevent site runoff flowing to the Conservation Area (CA). In view of the implementation of water quality mitigation measures, the site was generally order and no water quality impact was observed, it is considered that the exceedances were unlikely caused by the works under the Project.

ENVIRONMENTAL COMPLAINT

ES.09. No environmental complaint was recorded or received in this Reporting Month. The statistics of environmental complaint are summarized in the following table.

Table ES-6 Environmental Complaint Summaries in the Reporting Month

Domantina Dania I	Environmental Complaint Statistics		
Reporting Period	Frequency	Cumulative	Complaint Nature
1 – 31 October 2018	0	0	NA

ES.010. In addition, no complaints received and emergency events relating to violation of environmental legislation for illegal dumping and landfilling were received.

NOTIFICATION OF SUMMONS AND SUCCESSFUL PROSECUTIONS

ES.011. No environmental summons or successful prosecution was recorded in this Reporting Month. The statistics of summons or successful prosecutions are summarized in the following tables.

Table ES-7 Environmental Summons Summaries in the Reporting Month

Donoutina Donio d	Environmental Summons Statistics		
Reporting Period	Frequency	Cumulative	Complaint Nature
1 – 31 October 2018	0	0	NA

Table ES-8 Environmental Prosecution Summaries in the Reporting Month

Donauting Daviad	Environmental Prosecution Statistics		
Reporting Period	Frequency	Cumulative	Complaint Nature
1 – 31 October 2018	0	0	NA



REPORTING CHANGE

ES.012. There were no reporting changes in the Reporting Month.

SITE INSPECTION

ES.013. In this Reporting Period, joint site inspections to evaluate the site environmental performance at *Contract 1* have been carried out by the RE, ET and the Contractor on 4th, 11th, 19th, 25th and 31st

October 2018. No non-compliance was noted during the site inspection. Furthermore, IEC attended a joint site inspection on 19th October 2018.

FUTURE KEY ISSUES

- ES.014. The Contractors should pay special attention on water quality mitigation measures and fully implement according to the ISEMM of the EM&A Manual, in particular in rainy season to prevent surface runoff with high SS content and other pollutants from flowing to local stream and Conservation Area (CA).
- ES.015. Moreover, air quality and construction noise are the major environmental issues as under the Project Works. Air quality mitigation measures such as wheel wash facilities, watering of haul roads and covering of dusty materials with tarpaulin sheet should be implemented as far as practicable. Construction noise mitigation measures such as use of movable noise barriers and Quality Powered Mechanical Equipment (QPME) should be properly provided to reduce construction noise impact.
- ES.016. Furthermore, daily cleaning and weekly tidiness shall be properly performed and maintained. In addition, mosquito control should be performed to prevent mosquito breeding on site.



Table of Contents

1	INTROD		1
	1.1	PROJECT BACKGROUND	1
	1.2	REPORT STRUCTURE	2
2		ZATION AND CONSTRUCTION PROGRESS OF THE WORKS CONTRACT-1	3
	2.1	WORKS CONTRACT-1 ORGANIZATION AND MANAGEMENT STRUCTURE	3
	2.2	CONSTRUCTION PROGRESS	3
	2.3 2.4	SUMMARY OF ENVIRONMENTAL SUBMISSIONS	3
		SUMMARY OF SUBMISSION UNDER THE ENVIRONMENTAL PERMIT REQUIREMENTS	3
3		RY OF IMPACT MONITORING REQUIREMENT	5
	3.1 3.2	GENERAL MONITORING PARAMETERS	5
	3.2	MONITORING PARAMETERS MONITORING LOCATIONS	5
	3.4	MONITORING FREQUENCY AND PERIOD	7
	3.5	MONITORING EQUIPMENT	8
	3.6	EQUIPMENT CALIBRATION	10
	3.7	DATA MANAGEMENT AND DATA QA/QC CONTROL	11
	3.8	DETERMINATION OF ACTION/LIMIT (A/L) LEVELS	11
4	AIR QUA	LITY	12
	4.1	MONITORING RESULTS	12
	4.2	AIR MONITORING EXCEEDANCE	12
5	CONSTR	UCTION NOISE	13
	5.1	MONITORING RESULTS	13
	5.2	NOISE MONITORING EXCEEDANCE	13
6	WATER (QUALITY	14
	6.1	MONITORING RESULTS	14
	6.2	WATER QUALITY MONITORING EXCEEDANCE	14
7	ECOLOG	GY MONITORING	16
	7.1	REQUIREMENT	16
	7.2	METHODOLOGY	16
	7.3	ECOLOGICAL MONITORING SURVEY FINDINGS	17
8		APE AND VISUAL	20
	8.1	REQUIREMENT Financial / Department of the District Property of Montey	20
	8.2	FINDINGS / DEFICIENCIES DURING SITE INSPECTION IN THE REPORTING MONTH	20
9		MANAGEMENT	21
	9.1	GENERAL WASTE MANAGEMENT	21
	9.2	RECORDS OF WASTE QUANTITIES	21
10		PECTION	22
	10.1 10.2	REQUIREMENT FINANCIA / DEFICIENCIES DUDING SITE INSPECTION DUTINE DEPORTING MONTH	22
		FINDINGS / DEFICIENCIES DURING SITE INSPECTION IN THE REPORTING MONTH	22
11		NMENTAL COMPLAINT AND NON-COMPLIANCE	24
	11.1	ENVIRONMENTAL COMPLAINT, SUMMONS AND PROSECUTION	24
12		ENTATION STATUS OF MITIGATION MEASURES	25
	12.1	GENERAL REQUIREMENTS	25
	12.2	TENTATIVE CONSTRUCTION ACTIVITIES IN THE COMING MONTH	25
	12.3	KEY ISSUES FOR THE COMING MONTH	26
13		USIONS AND RECOMMENTATIONS	27
	13.1 13.2	CONCLUSIONS	27 27
	13.4	RECOMMENDATIONS	41



LIST OF TABLES

TABLE 2-1	STATUS OF ENVIRONMENTAL LICENSES AND PERMITS
TABLE 2-2	STATUS OF SUBMISSION AS UNDER EP AND/OR FEP STIPULATION
TABLE 3-1	SUMMARY OF EM&A REQUIREMENTS
TABLE 3-2	DESIGNATED AIR QUALITY MONITORING LOCATION UNDER THE PROJECT
TABLE 3-3	AIR QUALITY MONITORING LOCATION AS RELATED THE WORKS CONTRACT-1
TABLE 3-4	DESIGNATED CONSTRUCTION NOISE MONITORING LOCATION UNDER THE PROJECT
TABLE 3-5	NOISE MONITORING LOCATION AS RELATED THE WORKS CONTRACT-1
TABLE 3-6	DESIGNATED WATER QUALITY MONITORING STATIONS UNDER THE PROJECT
TABLE 3-7	WATER QUALITY MONITORING STATION AS RELATED THE WORKS CONTRACT-1
TABLE 3-8	AIR QUALITY MONITORING EQUIPMENT
TABLE 3-9	NOISE MONITORING EQUIPMENT
TABLE 3-10	WATER QUALITY MONITORING EQUIPMENT
TABLE 3-11	ACTION AND LIMIT LEVELS FOR AIR QUALITY MONITORING
TABLE 3-12	ACTION AND LIMIT LEVELS FOR CONSTRUCTION NOISE
TABLE 3-13	ACTION AND LIMIT LEVELS FOR WATER QUALITY
TABLE 4-1	SUMMARY OF 24-HOUR AND 1-HOUR TSP MONITORING RESULTS AT ASR-1
TABLE 5-1	SUMMARY OF CONSTRUCTION NOISE MONITORING RESULTS, dB(A)
TABLE 6-1	SUMMARY OF WATER QUALITY MONITORING RESULTS – M3
TABLE 6-2	ACTION AND LIMIT (A/L) LEVELS EXCEEDANCE RECORD
TABLE 6-3	SUMMARY OF INVESTIGATION FINDING OF WATER QUALITY EXCEEDANCE IN THE REPORTING PERIOD
Table 7-1	ACTION AND LIMIT LEVELS FOR WET WOODLAND HABITATS MONITORING
TABLE 7-2	ACTION AND LIMIT LEVELS FOR NON-WET WOODLAND HABITATS MONITORING
TABLE 7-3	SCHEDULE OF FAUNAL SURVEYS IN EACH YEAR DURING CONSTRUCTION PHASE
TABLE 7-4	RESULT OF AVIFAUNA SURVEY
TABLE 7-5	RESULT OF REPTILE SURVEY
TABLE 7-6	RESULT OF AMPHIBIAN SURVEY
TABLE 7-7	RESULT OF BUTTERFLY SURVEY
TABLE 7-8	RESULT OF ODONATE SURVEY
TABLE 7-9	RESULT OF FRESHWATER COMMUNITIES SURVEY
Table 9-1	SUMMARY OF QUANTITIES OF INERT C&D MATERIALS
TABLE 9-2	SUMMARY OF QUANTITIES OF C&D WASTES
TABLE 10-1	SITE OBSERVATIONS FOR THE WORKS OF CONTRACT 1
TABLE 11-1	STATISTICAL SUMMARY OF ENVIRONMENTAL COMPLAINTS
TABLE 11-2	STATISTICAL SUMMARY OF ENVIRONMENTAL SUMMONS
TABLE 11-3	STATISTICAL SUMMARY OF ENVIRONMENTAL PROSECUTION
TABLE 12-1	ENVIRONMENTAL MITIGATION MEASURES



LIST OF APPENDICES

APPENDIX A	LAYOUT PLAN OF THE PROJECT
APPENDIX B	ORGANIZATION STRUCTURE AND CONTACT DETAILS OF RELEVANT PARTIES
APPENDIX C	THREE MONTHS ROLLING PROGRAMME
APPENDIX D	DESIGNATED MONITORING LOCATIONS AS RECOMMENDED IN THE APPROVED EM&A MANUAL
APPENDIX E	CALIBRATION CERTIFICATES OF MONITORING EQUIPMENT AND LABORATORY CERTIFICATE
APPENDIX F	EVENT AND ACTION PLAN OF AIR QUALITY, NOISE AND WATER QUALITY
APPENDIX G	MONITORING SCHEDULES OF THE REPORTING MONTH AND COMING MONTH
APPENDIX H	MONITORING DATA OF 24-HOUR TSP AIR QUALITY, NOISE AND WATER QUALITY
APPENDIX I	GRAPHICAL PLOTS OF AIR QUALITY, NOISE AND WATER QUALITY
APPENDIX J	METEOROLOGICAL DATA OF THE REPORTING PERIOD
APPENDIX K	ECOLOGY SURVEY REPORT
APPENDIX L	LANDSCAPE & VISUAL INSPECTION CHECKLIST
APPENDIX M	MONTHLY SUMMARY WASTE FLOW TABLE
APPENDIX N	IMPLEMENTATION SCHEDULE FOR ENVIRONMENTAL MITIGATION MEASURES (ISEMM)



1 INTRODUCTION

1.1 PROJECT BACKGROUND

- 1.1.1 Civil Engineering and Development Department is the Project Proponent for the Project "Site Formation and Associated Infrastructural Works for Development of Columbarium, Crematorium and Related Facilities at Sandy Ridge Cemetery" (hereafter referred as "the Project"). The Project is a Designated Project to be implemented under Environmental Permit No. EP-534/2017. The layout plan of the Project is shown in Appendix A. To facilitate the Project management, the Project works were separated into three different Contracts which are described below sub-sections.
- 1.1.2 Contract No. CV/2016/10 Site Formation and Associated Infrastructural Works for Development of Columbarium at Sandy Ridge Cemetery (hereafter referred as "Contract 1"):-
 - Site formation of about 1.77 ha of land for the proposed pick-up and drop-off area for shuttle bus operation;
 - Upgrading of a section of 900m existing Sha Ling Road from 3m wide carriageway to 7.3m wide carriageway with footpath at both sides;
 - Construction of one EVA with a total length of about 160m;
 - Construction of noise barriers along Sha Ling Road;
 - Modification of junction between Man Kam To Road and Sha Ling Road;
 - Construction of a new pick up / drop off point at Man Kam To Road;
 - Relocation and construction of a new refuse collection point near junction between Man Kam To Road and Sha Ling Road;
 - Associated geotechnical works including cut and fill slopes, soil nailing works and retaining structures;
 - Associated drainage, sewerage and waterworks along Sha Ling Road; and
 - Associated landscaping works.
- 1.1.3 Contract No. CV/2017/02 Infrastructural Works at Man Kam To Road and Lin Ma Hang Road for Development of Columbarium at Sandy Ridge Cemetery (hereafter referred as "Contract 2"):-
 - Construction of a new road connecting Columbarium site to Crematorium site:
 - Construction of one EVA with a total length of about 300m;
 - Widening of a section of 1.4 km long Lin Ma Hang Road (between Man Kam To Road and Ping Yuen River) from 6m wide carriageway to 7.3m with 2m width footpath on both sides;
 - Provision of a pair of lay-by at Lin Ma Hang Road:
 - Construction of a new vehicular access connecting the Sheung Shui Landmark North PTI and Lung Sum Avenue:
 - Construction of covered walkway along Fanling Station Road;
 - Removal of planters and central divider along Fanling Station Road and San Wan Road;
 - Associated drainage, sewerage, waterworks and utility works along Man Kam To Road and Lin Ma Hang Road;
 - Associated geotechnical works including cut and fill slopes, soil nailing works and retaining structures; and
 - Associated landscaping works.
- 1.1.4 CEDD Contract No. (to be advised) (hereafter referred as "Contract 3"):-
 - Site Formation for the platform of the columbarium site;
 - Construction of two 2 at-grade access roads;
 - Construction of road junction between Man Kam To Road and the new access road;
 - Associated drainage, sewerage and waterworks along the two new access roads;
 - Associated geotechnical works including cut and fill slopes, soil nailing works and retaining structures; and
 - Associated landscaping works
- 1.1.5 Hsin Chong Tsun Yip Joint Venture (hereinafter "HCTYJV") has been awarded the *Works Contract 1* on 5 December 2017. According to the Contract requirement, HCTYJV shall take over the responsibility for part of Environmental Permit No. EP-534/2017 for ease of management, therefore application for Further Environmental Permit was submitted by HCTYJV to EPD on 26 January 2018 and Further Environmental Permit No. FEP-01/534/2017 was granted to HCTYJV by EPD on



23 February 2018. Major works to be executed under the Project shall include to the following:

A Designated Works under EP-534/2017

- (i) Site formation of about 8 hectares of land and associated drainage, sewerage and landscape works for development of Columbarium and Crematorium facilities at the Sandy Ridge Cemetery;
- (ii) Construction of a new road (about 600m) including a section of viaduct connecting the platform for Crematorium and Man Kam To Road and the pick-up/drop-off point at Man Kam To Road.;
- (iii) Widening of about 900m of the existing Sha Ling Road;
- (iv) Widening of about 1.4km of the existing Lin Ma Hang Road; and
- (v) Improvement works to the existing barging point at Siu Lam

Non-Designated Works

- (i) Construction of a sewage detention tank complete with odour and septicity control mechanism;
- (ii) Construction of noise barriers along Sha Ling Road;
- (iii) Construction of a new Refuse Collection Point (RCP) near the junction between Man Kam To Road and Sha Ling Road;
- (iv) Landscaping works (including both hard and soft landscape works);
- (v) Associated tree felling, transplanting and compensatory planting works;
- (vi) Associated street lighting, street furniture and road marking, etc.; and
- (vii) Other works which are specified in PS of the Contract.
- 1.1.6 Action-United Environmental Services & Consulting has been commissioned by HCTYJV as an Environmental Team to implement the EM&A programme in accordance with the approved EM&A Manual as well as the associated duties. As part of the EM&A programme, baseline monitoring to determine the ambient environmental conditions was completed before construction work commencement. The Baseline Monitoring Report (air, noise and water) certified by Environmental Team Leader (ETL) and verified by Independent Environmental Checker (IEC) was submitted to Environmental Protection Department (EPD) and it was approved by EPD on 25 October 2018.
- 1.1.7 This is the 3rd monthly Environmental Monitoring and Audit Report to reporting the monitoring results and inspection findings for the period from 1 to 31 October 2018.

1.2 REPORT STRUCTURE

- 1.2.1 The Monthly Environmental Monitoring and Audit (EM&A) Report is structured into the following sections:-
 - **Section 1** *Introduction*
 - **Section 2** *Project Organization and Construction Progress*
 - **Section 3** *Summary of Monitoring Requirements*
 - **Section 4** *Air Quality Monitoring Results*
 - **Section 5** *Noise Monitoring Results*
 - **Section 6** *Water Quality Monitoring Results*
 - **Section 7** *Ecology Monitoring Results*
 - **Section 8** *Landscape & Visual*
 - **Section 9** *Waste Management*
 - **Section 10** Site Inspections
 - **Section 11** *Environmental Complaints and Non-Compliance*
 - **Section 12** Implementation Status of Mitigation Measures
 - **Section 13** *Conclusions and Recommendation*



2 ORGANIZATION AND CONSTRUCTION PROGRESS OF THE WORKS CONTRACT-1

2.1 WORKS CONTRACT-1 ORGANIZATION AND MANAGEMENT STRUCTURE

2.1.1 Organization structure and contact details of relevant parties with respect to on-site environmental management are shown in *Appendix B*.

2.2 CONSTRUCTION PROGRESS

- 2.1.2 The three month rolling construction programme are enclosed in *Appendix C* and the major construction activities undertaken in this Reporting Month are listed below:-
 - General site clearance;
 - Bulk Excavation
 - Construction of temporary Site Office;
 - Construction of Cut Slope, installation of soil nailing and construction of surface channel;
 - Construction of retaining wall; and
 - Construction of fill slope.

2.3 SUMMARY OF ENVIRONMENTAL SUBMISSIONS

2.1.3 Summary of the relevant permits, licences, and/or notifications on environmental protection for this Project in this Reporting Month is presented in *Table 2-1*.

Table 2-1 Status of Environmental Licenses and Permits

Item	Description	License/ Permit ref no.	License/ Permit Status
1	Air Pollution Control (Construction	Ref. no. 428909	Valid
	Dust) Regulation	Acknowledged by EPD on 20/12/2017	
2	Chemical waste Producer	WPN: 5231-641-H3937-01	Valid
	Registration	Issued by EPD on 27/03/2018	
3	Water Pollution Control Ordinance	License no. WT00030795-2018	Valid
		Issued date: 9/5/2018	
		Expire Date: 31/5/2023	
4	Billing Account for Disposal of	Account no.: 7029769	Valid
	Construction Waste	Date approved: NA	
5	Construction Noise Permit	GW-RN0490-18	Valid
		Issued date: 14/9/2018	
		Expire Date: 18/11/2018	

2.4 SUMMARY OF SUBMISSION UNDER THE ENVIRONMENTAL PERMIT REQUIREMENTS

2.1.4 *Table 2-2* summarized the submission status under the EP and/or FEP stipulation in the Reporting Month.

Table 2-2 Status of Submission as under EP and/or FEP Stipulation

Item	EP and / or FEP Stipulation	Description	Situation
1		Management organization of: i) the	Submitted on 11 April 2018
		main construction companies; ii) ET;	
		and iii) IEC and the supporting team	
2	Condition 2.11 of the EP		Submitted on 12 April 2018
	and FEP	construction works; and ii) Location	
		plan of all construction works	
3	Condition 2.13 of EP and	Contamination Assessment Plan	Submitted on 11 Oct 2018
	Condition 2.12 of FEP	(CAP)	
4	Condition 2.14 of EP and	Grassland Reinstatement Plan	Submitted on 28 May 2018
	Condition 2.13 of FEP		·
5	Condition 2.15 of EP and	Vegetation Survey Report	Approved by EPD on 12 Oct
	Condition 2.14 of FEP		2018
6	Condition 2.16 of EP and	Vegetation Transplantation Proposal	Approved by EPD on 12 Oct
	Condition 2.15 of FEP		2018



Item	EP and / or FEP Stipulation	Description	Situation
7	Condition 2.18 of EP and	Woodland Compensation Plan	Submitted on 15 May 2018
	Condition 2.17 of FEP		
8	Condition 2.19 of EP and	Monitoring and Survey Plan for	Submitted on 9 May 2018
	Condition 2.18 of FEP	Golden-headed Cisticola	
9	Condition 2.22 of EP and	Landscape & Visual Mitigation and	Submitted on 18 May 2018
	Condition 2.20 of FEP	Tree Preservation Plan(s)	
10	Condition 2.24 of EP and	Traffic Noise Mitigation Plan	Submitted on 17 July 2018
	Condition 2.22 of FEP		
11	Condition 3.3 of the EP	Baseline Monitoring Report (Air,	Approved by EPD on 25 Oct
	and FEP	Noise and Water)	2018
12	Condition 4.2 of the EP	The Contract Internet website	Internet website address has
	and FEP		notified EPD on 15 Jun 2018



3 SUMMARY OF IMPACT MONITORING REQUIREMENT

3.1 GENERAL

- 3.1.1 The Environmental Monitoring and Audit requirements are set out in the Approved EM&A Manual. Environmental issues such as air quality, construction noise, water quality and ecology were identified as the key issues during the construction phase of the Project.
- 3.1.2 A summary of construction phase EM&A requirements are presented in the sub-sections below.

3.2 MONITORING PARAMETERS

- 3.2.1 The EM&A impact monitoring shall cover the following environmental aspect:
 - Air quality;
 - Construction noise;
 - Water quality; and
 - Ecology
- 3.2.2 A summary of the monitoring parameters is presented in *Table 3-1* below

Table 3-1 Summary of EM&A Requirements

Environmental Issue	Parameters	
Air Quality	1-hour TSP;24-hour TSP	
Noise	 Leq_(30min) during normal working hours.; and Leq_(15min) during the construction works is undertaken in Restricted Hours 	
Water Quality	In-situ Measurements Dissolved Oxygen Concentration (mg/L) & Saturation (%); Temperature (°C); Turbidity (NTU); Salinity (ppm) pH unit; Water depth (m); and Stream Flow Velocity (m/sec). Laboratory Analysis Suspended Solids (mg/L)	
Ecology	Ecologically sensitive habitats (wetland habitats and non-wetland habitats	

3.3 MONITORING LOCATIONS

- 3.3.1 According to the Approved EM&A Manual of the Project Site Formation and Associated Infrastructural Works for Development of Columbarium, Crematorium and Related Facilities at Sandy Ridge Cemetery, the designated monitoring locations for air quality, noise, water quality and ecology under the monitoring programme, is shown in Appendix D.
- 3.3.2 Since the Project was divided into three Works Contracts and all Contracts will be commenced at different time, the construction phase impact monitoring will only be performed at the Contract-related monitoring stations upon commencement of each Contract Works.

Air Quality

3.3.3 There were three (3) air quality monitoring stations / air quality sensitive receivers (ASR) recommended in the Approved EM&A Manual Section 5.6.1.1. The designated air quality monitoring locations were listed in *Table 3-2* and illustrated in *Appendix D*.

Table 3-2 Designated Air Quality Monitoring Location under the Project

Location ID	ASR ID in EIA	Description Location	
ASR-1	A1	Village House along Man Kam	Sha Ling Village House No.6
		To Road	
ASR-2	A2	Village House at San Uk Ling	San Uk Ling Village House



Location ID	ASR ID in EIA	Description	Location
			No.1
ASR-3	A3	Village House at Muk Wu Nga Yiu	Muk Wu Nga Yiu House No.28

3.3.4 Based on rationale in Section 3.3.2, the Contract-related air quality monitoring location under construction phase of Contract 1 is shown in *Table 3-3*.

Table 3-3 Air Quality Monitoring Location as Related the Works Contract-1

Location ID	ASR ID in EIA	Description	Location
ASR-1	A1	Village House along Man Kam	Sha Ling Village House No.6
		To Road	

- 3.3.5 If the designated monitoring location is required to relocate, alternative monitoring location shall meet the following criteria:
 - i) Be at the site boundary or such locations close to the major dust emission source;
 - ii) Close to the sensitive receptors;
 - iii) Take into account the prevailing meteorological conditions;
 - iv) For monitoring location located in the vicinity of the ASRs, care shall be taken to cause minimal disturbance to the occupants during monitoring.
 - v) When positioning the HVS, the following points shall be noted:
 - a. a horizontal platform with appropriate support to secure the samples against gusty wind shall be provided;
 - b. no two samplers shall be placed less than 2m apart;
 - c. the distance between the HVS and an obstacle, such as buildings, must be at least twice the height that the obstacle protrudes above the HVS;
 - d. a minimum of 2 m separation from walls, parapets and penthouses is required for HVS at the rooftop;
 - e. a minimum of 2 m separation from any supporting structure, measures horizontally is required;
 - f. no furnace or incinerator flue is nearby;
 - g. airflow around the sampler is unrestricted;
 - h. the HVS is more than 20 m from the dripline;
 - i. any wire fence and gate to protect the HVS, shall not cause any obstruction during monitoring;
 - j. permission must be obtained to set up the HVS and to obtain access to the monitoring stations; and
 - k. a secured supply of electricity is needed to operate the HVS.
- 3.3.6 Alternative monitoring location shall agree with IEC and seek for EPD approval.

Construction Noise

3.3.7 There were are four (4) noise monitoring locations / noise sensitive receivers (NSR) recommended in the Approved EM&A Manual Section 6.5.1.1. Site visits were conducted by the Contractor and ET on 6th & 10th April 2018 to review and study sensitive receivers at surrounding and adjacent to the Project. Four designated noise monitoring locations recommended in the Approved EM&A Manual were identified during the site visits. They were listed in *Table 3-4* and shown in *Appendix D*.

Table 3-4 Designated Construction Noise Monitoring Location under the Project

Location ID	NSR ID in EIA	Description	Location
CN-1	N5-2	Village house to the west of	Village house to the west of Sha
		Sha Ling Road	Ling Road (free field condition)
CN-2	N9-1	Village house to the north of	Sha Ling Village House No. 25
		Man Kam To Road	(free field condition)
CN-3	N18-5	Village house near San Uk	San Uk Ling Village House No.
		Ling	18 (free field condition)
CN-4	N21-4	Village house of Muk Wu	Muk Wu Village House No. 267



Location ID	NSR ID in EIA	Description	Location
			(1m façade from the building)

3.3.8 Based on rationale in Section 3.3.2, the Contract-related noise monitoring location under construction phase of Contract 1 is listed in *Table 3-5*.

Table 3-5 Noise Monitoring Location as Related the Works Contract-1

Location ID	ASR ID in EIA	Description	Location
CN-1	N5-2	Village house to the west of Sha Ling Road	Village house to the west of Sha Ling Road (free field condition)
CN-2	N9-1	Village house to the north of Man Kam To Road	Sha Ling Village House No. 25 (free field condition)

Water Quality

3.3.9 There were four (4) water quality monitoring locations recommended in the Approved EM&A Manual Section 7.6.1.2. The locations and coordinates of water quality monitoring were listed in *Table 3-6* and illustrated in *Appendix D*.

Table 3-6 Designated Water Quality Monitoring Stations under the Project

Proposed	Co-ordinates		D	
Location ID	North	East	Description	
M1	843 431	831 308	Midstream of Nam Hang Stream	
M2	843 840	831 101	Downstream of Nam Hang Stream	
M3	843 509	830 040	Wetland in the Conservation Area (CA) near Yuen Leng Chai	
M4	843 997	831 783	Watercourse across Lin Ma Hang Road, running from east of San Uk Ling to Man Kam To Boundary Control Point	

3.3.10 Based on rationale in Section 3.3.2, the Contract-related water quality monitoring station under construction phase of Contract 1 is listed in *Table 3-7*.

Table 3-7 Water Quality Monitoring Station as Related the Works Contract-1

Proposed	Co-ordinates		Description
Location ID	North	East	Description
M3	843 509	830 040	Wetland in the Conservation Area (CA) near Yuen Leng Chai

3.4 MONITORING FREQUENCY AND PERIOD

3.4.1 The requirements of impact monitoring were stipulated in *Sections 5.8.1.1*, *6.7.1.1* and *7.8.1.4* of the approved *EM&A Manual* and presented as follows.

Air Quality Monitoring

- 3.4.2 Monitoring frequency for air quality impact monitoring is as follows:
 - 1-Hour TSP 3 sets of 1-hour TSP monitoring shall be carried out once every six days during construction periods
 - 24-Hour TSP Once 24-hour TSP monitoring shall be carried out every six days during construction periods

Noise Monitoring

3.4.3 Noise impact monitoring shall be carried out once per week during construction periods. The noise measurement for the time period between 0700 and 1900 hours shall be measured in terms of L_{eq} (30 minutes) or 6 sets of L_{eq} (5mins).

Water Quality Monitoring

3.4.4 The monitoring frequency shall be 3 days per week during construction phase and the interval between two sets of monitoring shall not be less than 36 hours.



3.5 MONITORING EQUIPMENT

3.5.1 The monitoring equipment using for the EM&A program as proposed by the ET shall be verified by the IEC.

Air Quality Monitoring

- 3.5.2 The 24-hour and 1-hour TSP levels shall be measured by following the standard high volume sampling method as set out in the *Title 40 of the Code of Federal Regulations, Chapter 1 (Part 50), Appendix B.* If ET proposes to use a direct reading dust meter to measure 1-hour TSP levels, it shall submit sufficient information to IEC for approval.
- 3.5.3 The filter paper of 24-hour TSP measurement shall be determined by HOKLAS accredited laboratory.
- 3.5.4 All equipment used by ET for air quality monitoring is listed in *Table 3-8*.

Table 3-8 Air Quality Monitoring Equipment

Equipment	Model	
24-Hr TSP		
High Volume Air Sampler (HVAS)	TISCH High Volume Air Sampler, HVS Model TE-5170	
Calibration Kit	TISCH Model TE-5025A	
1-Hour TSP		
Portable Dust Meter	Sibata LD-3 Laser Dust monitor Particle Mass Profiler &	
Totalore Bust Wieter	Counter	

Wind Data Monitoring Equipment

- 3.5.5 According to the approved EM&A Manual, wind data monitoring equipment shall also be provided and set up for logging wind speed and wind direction near the dust monitoring locations. The equipment installation location shall be proposed by the ET and agreed with the IEC. For installation and operation of wind data monitoring equipment, the following points shall be observed:
 - 1) The wind sensors should be installed 10 m above ground so that they are clear of obstructions or turbulence caused by buildings.
 - 2) The wind data should be captured by a data logger. The data shall be downloaded for analysis at least once a month.
 - 3) The wind data monitoring equipment should be re-calibrated at least once every six months.
 - 4) Wind direction should be divided into 16 sectors of 22.5 degrees each.
- 3.5.6 ET has liaised with the premises owners/ landlords to grant the permission for the HVS installation. However, they rejected to set up wind data monitoring equipment installation in their premises.
- 3.5.7 Under this situation, the ET proposed to obtain representative wind data from the Hong Kong Observatory Ta Kwu Ling Weather Station. Ta Kwu Ling Station is located near the Project site which situated at the sea level above 15mPD and the wind data monitoring equipment is installed 10 m above the existing ground.

Noise Monitoring

- 3.5.8 Sound level meter in compliance with the International Electrotechnical Commission Publications 651: 1979 (Type 1) and 804: 1985 (Type 1) specifications shall be used for carrying out the noise monitoring. The sound level meter shall be checked using an acoustic calibrator. The wind speed shall be checked with a portable wind speed meter capable of measuring the wind speed in ms⁻¹ before each noise monitoring event. Noise measurements should not be made in fog, rain, wind with a steady speed exceeding 5 m s⁻¹ or wind with gusts exceeding 10 m s⁻¹.
- 3.5.9 Noise monitoring equipment used for impact monitoring is listed in *Table 3-9*.



Table 3-9 Noise Monitoring Equipment

Equipment	Model
Integrating Sound Level Meter	B&K Type 2238
Calibrator	B&K Type 4231
Portable Wind Speed Indicator	Testo Anemometer

3.5.10 Sound level meters listed above comply with the *International Electrotechnical Commission Publications 651: 1979 (Type 1)* and *804: 1985 (Type 1)* specifications, as recommended in TM issued under the NCO.

Water Quality Monitoring

3.5.11 Water quality parameters include dissolved oxygen, water temperature & depth, turbidity, salinity, pH and stream flow velocity shall be measured *in-situ*, and suspended solids shall be analyzed by a HOKLAS-accredited testing laboratory.

Dissolved Oxygen and Temperature Measurement

- 3.5.12 The dissolved oxygen (DO) measuring instruments should be portable and weatherproof. The equipment should also complete with cable and sensor, and DC power source. It should be capable of measuring:
 - A DO level in the range of 0 20 mg/L and 0 200% saturation; and
 - A temperature of 0 45 degree Celsius.
- 3.5.13 The equipment should have a membrane electrode with automatic temperature compensation complete with a cable.
- 3.5.14 Should salinity compensation not be built-in to the DO equipment, in-situ salinity should be measured to calibrate the DO measuring instruments prior to each measurement.

Turbidity Measurement

3.5.15 The turbidity measuring instruments should be a portable and weatherproof with DC power source. It should have a photoelectric sensor capable of measuring turbidity level between 0–1000 NTU (for example, Hach model 2100Q or an approved similar instrument).

Salinity Measurement

3.5.16 A portable salinometer capable of measuring salinity in the range of 0–40 parts per thousand (ppt) should be provided for measuring salinity of the water at each monitoring location.

pH Measurement

3.5.17 A portable pH meter capable of measuring a range between 0.0 and 14.0 should be provided to measure pH under the specified conditions accordingly to the APHA Standard Methods.

Water Depth Measurement

3.5.18 A portable, battery-operated echo sounder or an approved similar instrument should be used for water depths determination at each designated monitoring station.

Stream Flow Velocity Equipment

3.5.19 Since the EM&A Manuals do not specified instrument to use stream flow velocity measurement, the monitoring of stream flow velocity is therefore proposed to be conducted by using a flow probe which is a digital water velocity meter.

Water Sampling Equipment

3.5.20 A water sampler is required for suspended solid (SS) monitoring. A water sampler e.g. Kahlsico Water Sampler, which is a transparent PVC cylinder with capacity not less than 2 litres, will be used for water sampling if water depth over than 0.5m.



3.5.21 For sampling from very shallow water depths e.g. <0.5 m, water sample will be collected from water surface below 100mm using plastic bottle to avoid inclusion of bottom sediment or humus. Moreover, Teflon/stainless steel bailer or self-made sampling buckets maybe used for water sampling. The equipment used for sampling will be depended the sampling location and depth situations.

Sample Containers and Storage

- 3.5.22 Water samples for suspended solid should be stored in high density polythene bottles with no preservative added, packed in ice (cooled to 4°C without being frozen) and delivered to the laboratory within 24 hours of collection and be analyzed as soon as possible after collection.
- 3.5.23 Analysis of suspended solids should be carried out in a HOKLAS or other accredited laboratory. Water samples of about 1L should be collected at the monitoring stations for carrying out the laboratory suspended solids determination. The SS determination work should start within 24 hours after collection of the water samples. The SS analyses should follow the *APHA Standard Methods* 2540D with Limit of Reporting of 2 mg/L.
- 3.5.24 Details of the equipment used for water quality monitoring are listed in *Table 3-10* below.

Table 3-10 Water Quality Monitoring Equipment

Equipment	Model
Water Depth Detector	Tape measures
Water Sampler	A 2-litre transparent PVC cylinder with latex cups at both ends or teflon/stainless steel bailer or self-made sampling bucket
Thermometer & DO meter	YSI 550A / YSI Pro 20
pH meter	AZ8685 pH meter
Turbidimeter	Hach 2100Q
Salinometer	Atago refractometer Atago S Salinity Meter / AZ8371 Salinity Meter
Stream Flow Velocity	FP211 Global Flow Probe
Sample Container	High density polythene bottles (provided by laboratory)
Storage Container	'Willow' 33-litter plastic cool box with Ice pad

3.5.25 Furthermore, Suspended solids (SS) analysis was carried out by *ALS Technichem (HK) Pty Ltd*, he is one a local HOKLAS-accredited laboratory

3.6 EQUIPMENT CALIBRATION

- 3.6.1 The HVAS is operated and calibrated on a regular basis in accordance with the manufacturer's instruction using Tisch Calibration Kit Model TE-5025A. Calibration would carry out in two month interval. The calibration data are properly documented and the records are maintained by ET for future reference. Furthermore, Tisch Calibration Kit will be calibrated by the manufacturer in yearly basis.
- 3.6.2 The 1-hour TSP meter calibrated by a local HOKLAS-accredited laboratory would be undertaken in yearly basis. Zero response of the equipment was checked before and after each monitoring event.
- 3.6.3 The sound level meter and acoustic calibrator are calibrated and certified by a laboratory accredited under HOKLAS or any other international accreditation scheme at yearly basis.
- 3.6.4 The multi-parameter Water Quality Monitoring System is calibrated by HOKLAS accredited laboratory of three month intervals.
- 3.6.5 All updated calibration certificates of the monitoring equipment used for the impact monitoring program in this Reporting Month are attached in *Appendix E*.



3.7 DATA MANAGEMENT AND DATA QA/QC CONTROL

- 3.7.1 The impact monitoring data are handled by the ET's systematic data recording and management, which complies with in-house Quality Management System. Standard Field Data Sheets (FDS) are used in the impact monitoring program.
- 3.7.2 The monitoring data recorded in the equipment e.g. 1-hour TSP meter, noise meter and Multi-parameter Water Quality Monitoring System are downloaded directly from the equipment at the end of each monitoring day. The downloaded monitoring data are input into a computerized database properly maintained by the ET. The laboratory results are input directly into the computerized database and QA/QC checked by personnel other than those who input the data. For monitoring activities require laboratory analysis, the local laboratory follows the QA/QC requirements as set out under the HOKLAS scheme for all laboratory testing.

3.8 DETERMINATION OF ACTION/LIMIT (A/L) LEVELS

3.8.1 The baseline monitoring results form the basis for determining the environmental acceptance criteria for the impact monitoring. the air quality, construction noise and water quality criteria, namely Action and Limit levels were established according to Approved EM&A Manual, and they are listed in *Tables 3-11, 3-12* and *3-13* below.

Table 3-11 Action and Limit Levels for Air Quality Monitoring

Monitoring Stations	Action Lev	vel (μg/m³)	Limit Level (µg/m³)		
Monitoring Stations	1-hour	24-hour	1-hour	24-hour	
ASR-1	331	181	500	260	

Table 3-12 Action and Limit Levels for Construction Noise

Time Period	Action Level	Limit Level
0700-1900 hours on normal	When one documented	> 75* dB(A)
weekdays	complaint is received	> /3 · dB(A)

Note: * Reduces to 70 dB(A) for schools and 65 dB(A) during the school examination periods.

Table 3-13 Action and Limit Levels for Water Quality

Manitanina	DO (ı	ng/L)	Turbidit	ty (NTU)	SS (n	ng/L)
Monitoring Location	Action Level	Limit Level	Action Level	Limit Level	Action Level	Limit Level
M3	4.58	4.49	5.6	5.9	9.3	9.5

Notes:

- For DO, non-compliance of the water quality limits occurs when monitoring result is lower than the limits
- For turbidity and SS, non-compliance of the water quality limits occurs when monitoring result is higher than the limits.
- 3.8.2 Should non-compliance of the environmental quality criteria occurs, remedial actions will be triggered according to the Event and Action Plan enclosed in *Appendix F*.



4 AIR QUALITY

4.1 MONITORING RESULTS

- 4.1.1 Air quality impact monitoring schedule was submitted to all relevant parties which shown in *Appendix G*.
- 4.1.2 In this Reporting Period, 6 occasions 24-hour TSP and 15 occasions 1-hour TSP of the air quality monitoring was undertaken at designated air quality monitoring location ASR-1. The monitoring results for 24-hour and 1-hour TSP are summarized in *Table 4-1*. The database of 24-hour TSP is shown in *Appendix H* and the graphical plots of 24-hour and 1-hour TSP result are shown in *Appendix I*.

Table 4-1 Summary of 24-hour and 1-hour TSP Monitoring Results at ASR-1

	24-hour			1-hour TSP (μ	g/m ³)	
Date	TSP $(\mu g/m^3)$	Date	Start Time	1 st hour measured	2 nd hour measured	3 rd hour measured
2-Oct-18	102	3-Oct-18	9:47	114	121	127
8-Oct-18	96	9-Oct-18	9:19	108	114	120
13-Oct-18	97	15-Oct-18	9:46	50	57	62
19-Oct-18	75	20-Oct-18	9:37	87	92	73
25-Oct-18	92	26-Oct-18	9:54	66	68	67
31-Oct-18	95					
Average	93	Avera	ge		88	
(Range)	(75 - 102)	(Rang	ge)		(50 - 127)	

4.1.3 The meteorological data during the impact monitoring days are summarized in *Appendix J*.

4.2 AIR MONITORING EXCEEDANCE

4.2.1 As shown in *Table 4-1*, the monitoring results of 24-hour and 1-hour TSP monitoring in the Reporting Month were well below the Action Level. No Notification of Exceedance (NOE) of air quality monitoring criteria was issued and therefore corrective action was not required.



5 CONSTRUCTION NOISE

5.1 MONITORING RESULTS

- 5.1.1 Noise impact monitoring schedule was submitted to all relevant parties which shown in *Appendix G*.
- 5.1.2 In this Reporting Month, 4 occasions of noise monitoring were undertaken at designated noise monitoring location CN-1. The sound level were set in a free field situation, and therefore a façade correction of +3dB(A) has been added according to acoustical principles and EPD guidelines. Since the distance of current construction works of Contract 1 over 300m from CN-2, noise monitoring was not performed at that location in this Reporting Month. The monitoring result of noise monitoring is show in *Table 5-1* and the graphical plots are shown in *Appendix I*.

Table 5-1 Summary of Construction Noise Monitoring Results, dB(A) – CN1

Date	Start Time	1 st Leq _{5min}	2 nd Leq _{5min}	3 rd Leq _{5min}	4 th Leq _{5min}	5 th Leq _{5min}	6 th Leq _{5min}	Leq _{30min}	Corrected* Leq _{30min}
3-Oct-18	9:50	61.8	62.7	61.5	61.8	62.7	60.7	62	65
9-Oct-18	9:16	69.8	72.5	68.2	70.2	67.3	69.4	70	73
15-Oct-18	9:43	67.1	67.1	64.5	61.7	65.5	62.9	65	68
26-Oct-18	10:00	60.0	65.7	67.5	68.3	66.7	70.8	68	71
Limit Level -					75				

^(*) A façade correction of +3dB(A) has been added according to acoustical principles and EPD guidelines.

5.1.3 Prior and after noise monitoring, the accuracy of the sound level meter has been checked by an acoustic calibrator to ensure the measurement within acceptance range of ±0.5dB. Moreover, wind speed checked by portable wind speed meter has been performed before noise monitoring. No noise measurement was performed in fog, rain, wind with a steady speed exceeding 5 m s⁻¹ or wind with gusts exceeding 10 m s⁻¹.

5.2 NOISE MONITORING EXCEEDANCE

5.2.1 As shown in *Table 5-1*, no noise monitoring results exceeded the Limit Level in the Reporting Month. No Notification of Exceedance (NOE) of construction noise criterion was issued and no corrective action was therefore required.



6 WATER QUALITY

6.1 MONITORING RESULTS

- 6.1.1 Water quality impact monitoring schedule was submitted to all relevant parties which shown in *Appendix G*.
- 6.1.2 In the Reporting Month, a total of *14* monitoring days were carried out at designated monitoring station M3 for water quality impact monitoring. The monitoring result of key parameters including Dissolved Oxygen, Turbidity and Suspended Solids are summarized in *Table 6-1*. Detailed monitoring results including in-situ measurements and laboratory analysis data are shown in *Appendix H* and graphical plots for monitoring result are shown in *Appendix I*.

Table 6-1 Summary of Water Quality Monitoring Results – M3

		Parameters	
Date	DO (Averaged) (mg/L)	Turbidity (Averaged) (NTU)	Suspended Solids (Averaged) (mg/L)
2-Oct-18	4.76	8.0	6.0
4-Oct-18	4.92	5.5	8.5
6-Oct-18	5.22	5.6	6.5
9-Oct-18	4.63	5.6	9.0
11-Oct-18	4.64	<u>7.8</u>	7.0
13-Oct-18	5.40	5.3	6.0
16-Oct-18	5.66	4.0	3.0
18-Oct-18	5.31	5.5	5.0
20-Oct-18	5.81	5.3	3.0
23-Oct-18	5.40	5.3	8.5
25-Oct-18	5.10	7.9	<u>11.5</u>
27-Oct-18	5.98	4.4	8.0
29-Oct-18	5.50	4.9	4.5
31-Oct-18	5.13	5.2	4.5

Remarks: bold and underline indicated Limit Level exceedance

6.1.3 During the Reporting Month, field measurements at M3 showed that temperature of stream water were within 23.0°C to 27.1°C, no salinity concentrations was detected, pH values within 6.7 to 8.7 and the stream flow velocity between 0.1 and 0.2 m/sec.

6.2 WATER QUALITY MONITORING EXCEEDANCE

6.2.1 In this Reporting Period, a total of four (4) Limit Level exceedances, including three (3) Limit Level exceedances of turbidity and one (1) Limit Level exceedances of Suspended Solids were recorded at M3 they are summarized in *Table 6-2*.

Table 6-2 Action and Limit (A/L) Levels Exceedance Record

Station	D	o	Turb	oidity	s			Exceedance exceedance		
	Action	Limit	Action	Limit	Action	Limit	Action	Limit	Action	Limit
M3	0	0	0	3	0	1	0	4	0	0

6.2.2 Investigation for the cause of water quality exceedances have been undertaken by ET. Investigation results revealed that water quality mitigation measures have been implemented to minimize the water quality impact arising from contract works. Such as temporary bund and de-silting trench were installed at Retaining Wall RW1 to reduce the suspended solids content in runoff. Series of sheet pile was installed at site boundary to prevent site runoff flowing to the Conservation Area (CA). Moreover, exposed surface were covered by tarpaulin sheet as far as practicable. It was observed that construction of temporary drainage system was on-going and no muddy discharge was observed. In view of the implementation of water quality mitigation measures, the site was generally order and no water quality impact was observed, it is considered that the exceedances were unlikely caused by the works under the Project. Since the exceedances were concluded as not project-related, increase of monitoring frequency is not required according to EM&A Manual 7.8.1.3.



6.2.3 Notifications of Exceedance (NOE) were issued to relevant parties upon confirmation of the monitoring result. The exceedance investigation findings are summarized in *Table 6-3*.

Table 6-3 Summary of Investigation Finding of Water Quality Exceedance in the Reporting Period

Date of Exceedance	Exceeded Parameter	Cause of Water Quality Exceedance In Brief
2 and 11 October 2018	NTU	In our investigation, HCTY-JV had implemented water quality mitigation measures. Having reviewed the monitoring data, there was no exceedance of Suspended Solids (SS) and the turbidity level is within the respective baseline range. In view of the implementation of water quality mitigation measures, the site was generally order and no water quality impact was observed, it is considered that the exceedances were unlikely caused by the works under the Project.
25 October 2018	NTU & SS	In our investigation, HCTY-JV had implemented water quality mitigation measures. In view of the implementation of water quality mitigation measures, the site was generally order and no water quality impact was observed, it is considered that the exceedances were unlikely caused by the works under the Project.

6.2.4 Although the exceedances were concluded not related the works under Contract 1, the Contractor was reminded to fully implement water quality mitigation measures such as exposed surface and area with low operation frequency should be covered by impervious sheeting. Moreover, temporary drainage and collection system for site runoff should be fully accomplished as soon as possible which could highly reduce water quality impact to the surrounding watercourse and ecosystem.



7 ECOLOGY MONITORING

7.1 REQUIREMENT

- 7.1.1 According to approved EIA report (AEIAR-198/2016), habitat types within project boundary comprise of watercourse, grassland, upland grassland, plantation, woodland and developed area. Natural habitats were of moderate ecological value in terms of species diversity, species rarity, species abundance, ecological linkage as well as nursery. Moreover, 0.3ha of wet woodland on the northern side of Sandy Ridge was deemed habitat with high ecological value. Four types of habitats were regarded as ecologically sensitive habitats, namely wet woodland, watercourses, upland grassland and woodland. Considering human disturbance in upcoming construction and operation phases, ecologically sensitive habitats shall be monitored in accordance with EM&A Manual.
- 7.1.2 The objective of ecologically sensitive habitats monitoring is to evaluate the effectiveness of measures to minimize impacts on concerned habitats from disturbance and pollution. In order to monitor the effectiveness of the measures to the minimize impact on ecologically sensitive habitats from disturbance and pollution, monthly monitoring during construction and operation phases is required as specified in EM&A Manual. Standard faunal transect and sampling surveys cover both wetland habitats (wet woodland and watercourse) and non-wetland habitats (upland grassland and woodland).

7.2 METHODOLOGY

7.2.1 Wetland habitats include wet woodland and watercourses. Monitoring surveys using standardized quantitative methodology will conduct at fixed points. For seasonal watercourse, the survey will be conducted whenever the habitat appears. Measures to respond to decreases in numbers of aquatic fauna using the wetland habitats and Action/Limit levels to trigger these measures are detailed in *Table 7-1*.

Table 7-1 Action and Limit Levels for Wet Woodland Habitats Monitoring

Action Level	Response	Limit Level	Response
	C	taxa diversity by	Investigate cause and if cause identified as related to the project instigate remedial action.

Remarks: Action and Limit Levels and Responses to Evidence of Declines in Aquatic Fauna

7.2.2 Non-wetland habitats consist of upland grassland and woodland. Monthly quantitative surveys of non-aquatic fauna will be conducted using standard route transect counts. Measures to respond to decreases in numbers of non-aquatic fauna using the non-wetland habitats and Action/Limit levels to trigger these measures are detailed in *Table 7-2*.

Table 7-2 Action and Limit Levels for Non-Wet Woodland Habitats Monitoring

Action Level	Response	Limit Level	Response
		species diversity	Investigate cause and if cause identified as related to the project instigate remedial action.

Remarks: Action and Limit Levels and Responses to Evidence of Declines in Non-Aquatic Fauna

7.2.3 The ecological survey includes all taxa being investigated in accordance with EIA report. Schedule of faunal surveys in each year during construction phase is presented in *Table 7-3*.



Table 7-3 Schedule of Faunal Surveys in each year During Construction Phase

Month	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Mammals	$\sqrt{}$											
Birds (day)	$\sqrt{}$					V						
Birds (night)												
Herpetofauna												
Dragonflies												
Butterflies												
Aquatic fauna	$\sqrt{}$											$\sqrt{}$

Mammal Survey

7.2.4 Mammal surveys will be conducted along the proposed transects (shown in Appendix D of the survey report) during both daytime and night time periods. Along with direct observations, other field signs, such as scats and tracks, will be searched and recorded if present.

Bird Survey

7.2.5 Bird surveys will be conducted along the transects (shown in Appendix D of the survey report) during the surveys, species and their vocalizing individuals recorded will be enumerated and recorded according to the habitat(s) they are utilizing.

Herpetofauna Survey

7.2.6 Reptile and amphibian surveys will be conducted along transects (shown in Appendix D of the survey report) during surveys careful searches of appropriate microhabitats and refugia for reptiles and their vocalizing individuals will be undertaken and all reptiles observed will be identified and counted.

Dragonfly and Butterfly Survey

7.2.7 Dragonfly and Butterfly surveys will be conducted along transects (shown in Appendix D of the survey report) during surveys all dragonflies and Butterflies seen will be identified and counted as accurately as possible.

Aquatic Fauna Survey

- 7.2.8 Freshwater fishes and macro-invertebrates will be recorded by direct observation. All species trapped/recorded will be enumerated and identified (to the lowest taxonomic level possible), and the species of conservation importance photographed.
- 7.2.9 After each ecological monitoring survey, a monthly report of the survey result and data collected will be provided with reference to EM&A Manual. An annual analysis of data will be carried out in order to study if there is any significant reduction in taxa diversity and abundance.

7.3 ECOLOGICAL MONITORING SURVEY FINDINGS

7.3.1 In the Reporting Month, ecological monitoring was undertaken on 4th October 2018. The weather of monitoring day was fine. The monitoring survey was included day and night sections, covering wetland and non-wetland areas. The survey was conducted by transect and fixed points. All species seen will be identified and counted as accurately as possible. Results of the monitoring survey are presented below:

<u>Mammal</u>

7.3.2 There was no mammal recorded in the monitoring area

Birds

7.3.3 There were a total of 32 bird individuals from 10 species recorded during the survey.

<u>Herpetofauna</u>

7.3.4 There were no reptiles recorded in the monitoring area. There was two amphibian (Kaloula



pulchra ,Asiatic Painted Frog, 花狹口蛙) and Microhyla fissipes, Ornate Pigmy Frog, 飾紋姬蛙) found in the monitoring area.

Dragonfly

7.3.5 There were a total of 13 odonate individuals from 2 species.

Butterfly

7.3.6 There were a total of 3 butterfly individuals from 3 species recorded.

Aquatic Fauna Survey (Freshwater communities)

- 7.3.7 2 crabs of conservation importance Somanniathelphusa zanklon (鐮刀束腰蟹) were found in marsh.
- 7.3.8 The summaries of faunal survey result are shown in *Tables 7-4*, 7-5, 7-6, 7-8 and 7-9.

Table 7-4 Result of Avifauna Survey

Scientific Name	English Name	Chinese Name	Conservation Status	Non- wetland	Wetland
Apus nipalensis	House Swift	小白腰雨燕		15	
Lanius schach	Long-tailed Shrike	棕背伯勞			1
Dicrurus macrocercus	Black Drongo	黑卷尾		1	
Corvus macrorhynchos	Large-billed Crow	大嘴烏鴉		2	
Pycnonotus jocosus	Red-whiskered Bulbul	紅耳鵯		2	
Pycnonotus aurigaster	Sooty-headed Bulbul	白喉紅臀鵯		2	
Prinia inornata	Plain Prinia	純色鷦鶯			1
Garrulax chinensis	Black-throated Laughingthrush	黑喉噪鶥			2
Zosterops japonicus	Japanese White-eye	暗綠繡眼鳥		4	
Gracupica nigricollis	Black-collared Starling	黑領椋鳥			2

Table 7-5 Result of Reptile Survey

Scientific Name	Common Name	Chinese Name	Non-wetland	Wetland

Table 7-6 Result of Amphibian Survey

Scientific Name	Common Name	Chinese Name	Conservation Status	Non- wetland	Wetland
Kaloula pulchra	Asiatic Painted Frog, Piebald Digging Frog	花狹口蛙			1
Microhyla fissipes	Ornate Pigmy Frog, Ornate Ricefrog, Ornamented Pygmy Frog	飾紋姬蛙		1	

Table 7-7 Result of Butterfly Survey

Scientific Name	Common Name	Chinese Name	Non- wetland	Wetland
Parnara guttata	Common Straight Swift	直紋稻弄蝶	1	
Rapala manea	Slate Flash	燕灰蝶	1	
Abisara echerius	Plum Judy	蛇目褐蜆蝶		1



Table 7-8 Result of Odonate Survey

Scientific Name	Common Name	Chinese Name	Conservation Status	Non- wetland	Wetland
Ceriagrion auranticum	Orange-tailed Sprite	琉球橘黃蟌		1	
Pantala flavescens	Wandering Glider	黃蜻		12	

Table 7-9 Result of Freshwater Communities Survey

Scientific Name	Common Name	Chinese Name	Conservation Status	4-Oct-18
<u>Somanniathelphus</u> <u>a zanklon</u>		鐮刀束腰蟹	Fellowes et al. (2002): GC	2

- 7.3.9 The detailed survey report is attached in *Appendix K*.
- 7.3.10 The tentative ecology inspection and monitoring in the next reporting period (November 2018) is scheduled on 15th November 2018.



8 LANDSCAPE AND VISUAL

8.1 REQUIREMENT

- 8.1.1 The EIA has recommended EM&A for landscape and visual resources to be undertaken during the design, construction and operational stages of the project. The design, implementation and maintenance of landscape mitigation measures is a key aspect of this and should be checked to ensure that they are fully realized and that potential conflicts between the proposed landscape measures and any other project works let its are resolved at the earliest possible date and without compromise to the intention of the mitigation measures. In addition, implementation of the mitigation measures recommended by the EIA will be monitored through the site audit programme.
- 8.1.2 A number of mitigation measures to ameliorate the landscape and visual impacts of the Project implementation is summarized in the EMIS of *Appendix 13.1* of the EIA Report.
- 8.1.3 The landscape and visual mitigation measures proposed should be incorporated in the landscape and engineering design. Mitigation measures to be implemented during construction should be adopted from the start of construction and be in place throughout the entire construction period. Mitigation measures to be implemented during operation should be integrated into the detailed design and built as part of the construction works so that they are in place on commissioning of the Project. Tree transplantation and compensatory planting should be carried out as early as possible in the Project with transplantation carried out prior to construction starting in any particular area.
- 8.1.4 During construction phase, Landscape & Visual Monitoring of the contractor's operations should be conducted monthly and reported by ET, and countersigned by IEC.

8.2 FINDINGS / DEFICIENCIES DURING SITE INSPECTION IN THE REPORTING MONTH

8.2.1 In the Reporting Period, landscape & Visual inspection was carried out by the Registered Landscape Architect (RLA) on 29 October 2018. The findings / reminders recorded during the inspection are presented below:

Date	Findings and Reminder
29 October 2018	 Construction works were being started. According to 'Tree Preservation' No7/2015, 26a, Contractor was reminded to provide TPZ with proper and robust fence at the dripline of all retained trees. No works were allowed to undertake within the TPZ. Typhoon Mangkhut lead to fallen trees on site, contractor was reminded to remove these risk trees. Construction material was found placing next to the retained tree, the contractor is reminded to provide robust TPZ and do not place any construction material in it. Concrete leakage on the construction site was observed, contractor is reminded to keep the site clean and tidy. Raised soil level near root flare of tree was observed, as it may lead to suffocation of tree root, contractor is reminded to lower the soil level around the tree root flare.

8.2.2 Inspection checklist of Landscape & Visual signed by RLA is attached in *Appendix L*.



9 WASTE MANAGEMENT

9.1 GENERAL WASTE MANAGEMENT

9.1.1 Waste management was carried out by an on-site Environmental Officer or an Environmental Supervisor from time to time in accordance with the Waste Management Plan (WMP).

9.2 RECORDS OF WASTE QUANTITIES

- 9.2.1 All types of waste arising from the construction work are classified into the following:
 - Construction & Demolition (C&D) Material;
 - Chemical Waste:
 - General Refuse; and
 - Excavated Soil.
- 9.2.2 The quantities of waste for disposal in this Reporting Period are summarized in *Table 9-1* and *9-2* and the Monthly Summary Waste Flow Table is shown in *Appendix M*. Whenever possible, materials were reused on-site as far as practicable.

Table 9-1 Summary of Quantities of Inert C&D Materials

Type of Waste	Quantity	Disposal Location
C&D Materials (Inert) (m ³)	0	-
Reused in this Contract (Inert) (m ³)	2.982	Within the Contract working site
Reused in other Projects (Inert) (m ³)	0	-
Disposal as Public Fill (Inert) (m ³)	43.881	Tuen Mun Area 38

Table 9-2 Summary of Quantities of C&D Wastes

Type of Waste	Quantity	Disposal Location
Recycled Metal (kg)	0	-
Recycled Paper / Cardboard Packing (kg)	0	-
Recycled Plastic (kg)	0	-
Chemical Wastes (kg)	0	-
General Refuses (m ³)	0.298	NENT Landfill

9.2.3 Since canteen and/or kitchen are not allowed setting on the Project site, no domestic wastewater was generated from the Project.



10 SITE INSPECTION

10.1 REQUIREMENT

10.1.1 According to the approved Environmental Monitoring and Audit Manual, environmental site inspection should be formulated by the ET Leader. Regular environmental site inspections shall be carried out to assess the environmental performance once per week.

10.2 FINDINGS / DEFICIENCIES DURING SITE INSPECTION IN THE REPORTING MONTH

- 10.2.1 In the Reporting Period, joint site inspections to evaluate the site environmental performance carried out by the RE, ET and the Contractor was on 4th, 11th, 19th, 25th and 31st October 2018. Moreover, IEC attended a joint site inspection on 19th October 2018. No non-compliance was noted.
- 10.2.2 The findings / deficiencies that observed during the weekly site inspection are listed in *Table 10-1*.

Table 10-1 Site Observations for the Works of Contract-1

Date	Findings / Deficiencies	Follow-Up Status
4 October 2018	• The Contractor was reminded to spray water reguarly within site area for dust suppression.	Not required for reminder.
11 October 2018	• Chemical container without drip tray was observed. The Contractor should place the chemical container into drip tray to avoid land contamination.	Chemical container was removed to chemical storage area.
	 NRMM label was not observed for the excavator. The Contractor should display the NRMM label according the the NRMM regulation. 	NRMM label was displayed on excavator.
	• The Contractor was reminded to spray water regularly within site area and ensure dust mitigation measure for construction work such as slope drilling was properly	Not required for reminder.
	 implemented for dust suppression. The Contractor was reminded to provide sufficient amount of rubbish bin within site area for collecting general wastes. 	Not required for reminder.
	• The Contractor was reminded to clean the stagnant water in drip tray under generator.	Not required for reminder.
	• The Contractor was reminded to provide drip tray for generator within site area.	Not required for reminder.
	 The Contractor was reminded to provide proper mitigation measure on open slope for dust suppression. 	Not required for reminder.
19 October 2018	• Chemical containers were observed on the ground at work area of retaining wall. The Contractor should provide drip tray chemical containers to avoid oil leakage.	Drip tray was provided for the chemical containers.
25 October 2018	• Chemical containers were observed on the ground at CS11. The Contractor should provide drip tray to chemical containers to	• Drip tray was provided for the chemical containers.
	 avoid land contamination. The Contractor was reminded to dispose the empty cement bag properly to reduce dust 	Not required for reminder.
	impact.The Contractor was reminded to maintain good housekeeping on site.	Not required for reminder.



31 October	• Chemical containers were observed near	Drip tray was provided for
2018	site entrance. The Contractor should provide	the chemical containers.
	drip tray to chemical containers to avoid	
	land contamination.	 Not required for reminder.
	• The Contractor was reminded to dispose the	
	empty cement bag properly to reduce dust	
	impact.	• Not required for reminder.
	• The Contractor was reminded to maintain	•
	good housekeeping on site.	

- 10.2.3 The Contractor is reminded to cover the open slope as far as practicable to reduce turbid runoff generated during rainy days and ensure all site runoff are properly diverted and treated prior to discharge. Moreover, all temporary catch pits shall be maintained in good condition in order to reduce water impact during heavy rainfall.
- 10.2.4 Moreover, removal of stagnant water within site areas should be conducted after rain to prevent mosquito breeding. In addition, all retained trees within site area shall be properly protected by mean of tree protection zone to avoid damage from work.



11 ENVIRONMENTAL COMPLAINT AND NON-COMPLIANCE

11.1 Environmental Complaint, Summons and Prosecution

11.1.1 In the Reporting Period, no environmental complaint_was received. No summons and prosecution was lodged for the Contract. The statistical summary table of the environmental complaint, summons and prosecution are presented in *Tables 11-1*, *11-2* and *11-3*.

Table 11-1 Statistical Summary of Environmental Complaints

Donauting Davied	Environmental Complaint Statistics			
Reporting Period	Frequency	Cumulative	Complaint Nature	
1 – 31 October 2018	0	0	NA	

Table 11-2 Statistical Summary of Environmental Summons

Domontino Domio d	Environmental Summons Statistics			
Reporting Period	Frequency	Cumulative	Complaint Nature	
1 – 31 October 2018	0	0	NA	

Table 11-3 Statistical Summary of Environmental Prosecution

Reporting Period	Environmental Prosecution Statistics		
	Frequency	Cumulative	Complaint Nature
1 – 31 October 2018	0	0	NA

11.1.2 In addition, no complaints received and emergency events relating to violation of environmental legislation for illegal dumping and landfilling were received.



12 IMPLEMENTATION STATUS OF MITIGATION MEASURES

12.1 GENERAL REQUIREMENTS

- 12.1.1 The environmental mitigation measures that recommended in the Implementation Schedule for Environmental Mitigation Measures (ISEMM) in the approved EM&A Manual covered the issues of dust, noise, water and waste and they are summarized presented in *Appendix N*.
- 12.1.2 The Works of Contract 1 under the Project shall be implementing the required environmental mitigation measures according to the approved EM&A Manual subject to the site condition. Environmental mitigation measures implemented in this Reporting Month is summarized in *Table 12-1*.

Table 12-1 Environmental Mitigation Measures

Issues	Environmental Mitigation Measures
Water Quality	 Provided efficient silt removal facilities to reduce SS level before effluent discharge. Provided ditches, earth bunds or sand bag barriers to minimize polluted runoff. Temporary drainage was provided to prevent runoff going through site surface and minimize polluted runoff. Provided perimeter cut-off drains at site boundaries to intercept storm runoff from crossing the site. Exposed slopes surface were compacted and covered with tarpaulin or similar means Provided portable chemical toilets on site.
Air Quality	 Maintain damp / wet surface on access road. Maintain low vehicular speed within the works areas. Provided vehicle wheel washing facilities at each construction site exit; Provided water spraying for all active works area. Stockpiles of dusty material were covered with impervious sheeting. Provided workers to clear dusty materials at the vehicle entrance or exit regularly. Stockpile more than 20 bags of cement or dry pulverized fuel ash (PFA) has been covered entirely by impervious sheeting or placed in an area sheltered on the top and the 3 sides.
Noise	 Restricted operation time of plants from 07:00 to 19:00 on any working day except for Public Holiday and Sunday. Keep good maintenance of plants Placed noisy plants away from residence and school Provided noise barriers or hoarding to enclose the noisy plants or works Shut down the plants when not in used.
Waste and Chemical Management	 Provided on-site sorting prior to disposal Followed requirements and procedures of the "Trip-ticket System"
General	The site was generally kept tidy and clean.

12.2 TENTATIVE CONSTRUCTION ACTIVITIES IN THE COMING MONTH

- 12.2.1 According to the information provided by HCTYJV, the forthcoming construction activities for Contract 1 are listed below:
 - (i) General Site Clearance
 - (ii) Bulk Excavation
 - (iii) Construction of Temporary Site Office
 - (iv) Construction of Cut Slope, installation of soil nailing and construction of surface channel.
 - (v) Construction of retaining wall
 - (vi) Construction of fill slope



12.3 KEY ISSUES FOR THE COMING MONTH

- 12.3.1 Key issues to be considered in the coming month for the works of Contract 1 include:
 - Implementation of control measures for rainstorm;
 - Regular clearance of stagnant water during wet season;
 - Implementation of dust suppression measures at all times;
 - Potential wastewater quality impact due to surface runoff;
 - Potential fugitive dust quality impact due from the dry/loose/exposure soil surface/dusty material;
 - Ensure dust suppression measures are implemented properly;
 - Sediment catch-pits and silt removal facilities should be regularly maintained;
 - Discharge of site effluent to the nearby wetland is prohibited;
 - Nearby wetland prohibited stockpiling and/or disposal of materials;
 - Follow-up of improvement on general waste management issues; and
 - Implementation of construction noise preventative control measures.



13 CONCLUSIONS AND RECOMMENTATIONS

13.1 CONCLUSIONS

- 13.1.1 This is the 3rd monthly Environmental Monitoring and Audit Report presenting the monitoring results and inspection findings for the period of 1 to 31 October 2018.
- 13.1.2 No 24-hour or 1-hour TSP monitoring result that triggered the Action or Limit Levels was recorded. No NOEs or the associated corrective action was therefore required.
- 13.1.3 No noise complaint (which is an Action Level exceedance) was received and no construction noise measurement result that exceeded the Limit Level was recorded in this Reporting Month. No NOEs or the associated corrective actions were therefore issued.
- 13.1.4 For water quality monitoring, a total of 4 Limit Level (LL) exceedances, including 3 LL exceedance of turbidity and 1 LL exceedances of SS were recorded at designated monitoring location M3. Investigation results revealed that water quality mitigation measures have been implemented to minimize the water quality impact arising from contract works. Such as temporary bund and de-silting trench were installed at Retaining Wall RW1 to reduce the suspended solids content in runoff. Series of sheet pile was installed at site boundary to prevent site runoff flowing to the Conservation Area (CA). In view of the implementation of water quality mitigation measures, the site was generally order and no water quality impact was observed, it is considered that the exceedances were unlikely caused by the works under the Project.
- 13.1.5 Monthly ecological monitoring for sensitive habitat is undertaken on 4th October 2018. Moreover, Landscape and visual inspection was undertaken by the RLA on 29th October 2018.
- 13.1.6 In the Reporting Period, no environmental complaint, summons and prosecution was received. In addition, no complaints received and emergency events relating to violation of environmental legislation for illegal dumping and landfilling were received.
- 13.1.7 In the Reporting Period, joint site inspections to evaluate the site environmental performance were carried out by the RE, ET and the Contractor on 4th, 11th, 19th, 25th and 31st October 2018 and IEC attended joint site inspection on 19th October 2018. No non-compliance of environmental issue was recorded. In general, it was reminded that water quality mitigation measures should be fully implemented and good housekeeping practice should be maintained.

13.2 RECOMMENDATIONS

- 13.2.1 The Contractors should pay special attention on water quality mitigation measures and fully implement according to the ISEMM of the EM&A Manual, in particular in rainy season to prevent surface runoff with high SS content and other pollutants from flowing to local steam and Conservation Area (CA).
- 13.2.2 Construction noise would be a key environmental issue during construction phase of the Project. Noise mitigation measures such as using quiet plants and mobile noise barriers should be implemented in accordance with the EM&A requirement.
- 13.2.3 Since construction site under the Works of Contract 1 of the Project is located near villages, HCTYJV should fully implement air quality mitigation measures to reduce construction dust emission.
- 13.2.4 Furthermore, daily cleaning and weekly tidiness shall be properly performed and maintained. In addition, mosquito control should be performed to prevent mosquito breeding on site.




Appendix A

Layout Plan of the Project

Environmental Permit No.: EP-534/2017

環境許可證編號: EP-534/2017



Project Title: Site Formation and Associated Infrastructural Works for Development of Columbarium, Crematorium and Related Facilities at Sandy Ridge Cemetery

工程名稱:沙嶺墳場興建骨灰龕、火葬場及有關設施的工地平整及相關基建工程

Figure 1: Project Location Plan

圖1:項目位置圖


(This figure was prepared based on Figures 1.1-1.3 of the Approved EIA Report No. AEIAR-198/2016)


(本圖是根據環境影響評估報告編號 AEIAR-198/2016, 圖 1.1-1.3 編制)


Environmental Permit No.: EP-534/2017

環境許可證編號: EP-534/2017












Appendix B


Organization Structure and Contact Details of Relevant Parties



The Contract's Environmental Management Organization




Line of Communication






Organisation Chart of IEC Team



Professional and Technical Support







Contact Details of Key Personnel

Organization	Project Role	Name of Key Staff	Tel No.	Fax No.
CEDD	Employer	Joseph Wong	2762-5658	2714-0079
ARUP	Engineer's Representative	Steve Tang	6190-1513	2268-3950
ACUITY	Independent Environmental Checker	Ir. Leung CH Jacky	2698-6833	2698-9383
HCTYJV	Project Director	Mr. Kan Kwok Cheung	2358-2888	2633-4691
HCTYJV	Project Manager	Mr. Keniel Kwong	9863-0020	2633-4691
HCTYJV	Site Agent	Mr. Ho Man To	9620-9794	2633-4691
НСТҮЈУ	Site Engineer	Mr. James Leung	9308-1537	2633-4691
HCTYJV	Environmental Officer	Mr. Frankie Lam	6159-1140	2633-4691
HCTYJV	Safety Officer	Mr. Martin Kum	9202-5243	2633-4691
AUES	Environmental Team Leader	Mr. T.W. Tam	2959-6059	2959-6079
AUES	JES Environmental Consultant Mr. Ben Tam		2959-6059	2959-6079
AUES	Environmental Consultant	Ms. Nicola Hon	2959-6059	2959-6079
AUES	Environmental Site Inspector	Mr. Martin Li	2959-6059	2959-6079

Legend:

CEDD (Employer) – Civil Engineering and Development Department

ARUP (Engineer) – Ove Arup & Partners Hong Kong Limited

HCTYJV (Main Contractor) – Hsin Chong Tsun Yip Joint Venture

ACUITY (IEC) – Acuity Sustainability Consulting Limited

AUES (ET) – Action-United Environmental Services & Consulting



Appendix C

Three Months rolling Programme


Contract No. CV/2016/10 Hsin Chong Tsun Yip Joint Venture 3-month Rolling Programme (Oct 2018 to Dec 2018) Site Formation and Associated Infrastructural Works for Development of Columbarium at Sandy Ridge Cemetery 2199 days Fri 15/12/17 H Key Dates Fri 22/12/23 28 Subletting 239 days Fri 5/1/18 Fri 31/8/18 41 Preliminary Works 606 days Fri 15/12/17 Mon 12/8/19 Section 1 of the Works (Parts A1, A2 & A3) 837 days Fri 15/12/17 Mon 30/3/20 31 days Wed 28/2/18 Mon 9/4/18 Tree Survey and Report Submission Tree Felling and Tree Transplant 58 days Fri 4/5/18 Fri 13/7/18 Frection of Site Hoarding 30 days Thu 16/8/18 Wed 19/9/18 109 Temporary Drainage Works 90 days Thu 16/8/18 Tue 4/12/18 110 1 111 1 112 1 **Utilities Div ersion/Protection Works** 45 days Fri 15/12/17 Thu 8/2/18 Enquiries of Utilities As-built Record from UU Companies 45 days Fri 15/12/17 Thu 8/2/18 0 days Fri 15/12/17 Fri 15/12/17 Removal / Diversion of Existing 11kV Overhead Cable (By CLP) 0 days Fri 15/12/17 Fri 15/12/17 114 Ground Investigation and Geotechnical instrumentation for Commencement of Slopework 120 days Tue 20/3/18 Wed 15/8/18 Mobilization of GI Rig and Preparation Works 18 days Tue 20/3/18 Fri 13/4/18 Verification Drillholes (2 Nos., VDH1, 2) and Preliminary Results Submission 12 days Sat 14/4/18 Fri 27/4/18 Site Clearance for Vertification Drillholes (6 Nos., VDH7-9,16-18) 14 days Fri 4/5/18 Sat 19/5/18 118 Verification Drillholes (6 Nos., VDH7-9, 16-18) and Preliminary Results Submission 36 days Mon 21/5/18 Wed 4/7/18 119 **1** 120 **1** 24 days Mon 21/5/18 Inspection Pits (4 Nos., IP1-4) Tue 19/6/18 Geotechnical Instrumentation Required for Commencement of Slope Works 30 days Sat 14/4/18 Sat 19/5/18 121 Formal Report Submission and Verification of the Design of Cut and Fill Slope by PM 42 days Thu 5/7/18 Wed 15/8/18 Retaining Wall RW1 317 days Thu 16/8/18 Fri 13/9/19 27 days Thu 16/8/18 Excavation to Formation Level, Plate Load Test and Blinding Layer for Retaining Wall Bays 1-9 Sat 15/9/18 Excavation to Formation Level, Plate Load Test and Blinding Layer for Retaining Wall Bays 10-17 29 days Mon 17/9/18 Thu 25/10/18 125 11 days Thu 16/8/18 Temporary Access Road for Vechicular Access Tue 28/8/18 Base of Retaining Wall RW1 Bay 1-9 32 days Thu 30/8/18 Mon 8/10/18 Base of Retaining Wall RW1 Bay 10-17 32 days Tue 9/10/18 Sat 17/11/18 Wall Stem of Retaining Wall RW1 1-4 26 days Sat 8/9/18 Wed 10/10/18 Wall Stem of Retaining Wall RW1 Bay 5-10 (1st pour) 26 days Thu 11/10/18 Tue 13/11/18 36 days Wed 14/11/18 Wall Stem of Retaining Wall RW1 11-17 Thu 27/12/18 39 days Fri 28/12/18 Wall Stem of Retaining Wall RW1 Bay 5-10 (2nd pour) Fri 15/2/19 132 173 days Thu 13/9/18 Thu 18/4/19 Filter Laver behind RW1 133 111 days Fri 28/12/18 Erosion Control Mat at RW1 Mon 20/5/19 120 days Fri 28/12/18 Drainage and Maintenance Access in front of RW1 Thu 30/5/19 426 days Thu 11/10/18 Fill Slope FS1 Wed 25/3/20 396 days Wed 14/11/18 Fill Slope FS1 South (Section 12 at Drawing C1/GE/1030) Fri 20/3/20 75 days Wed 14/11/18 FS1 South Backfilling Stage 1 (~7.6m max, Section 12 up to +20 mPD) Fri 15/2/19 145 Fill Slope FS1 North (Section 14 at Drawing C1/GE/1030) 426 days Thu 11/10/18 Wed 25/3/20 FS1 North Backfilling Stage 1 (~5m height, Section 14 up to ~+20 mPD) 76 days Thu 11/10/18 Mon 14/1/19 154 496 days Mon 23/7/18 Road D and Pickup/Drop-Off Area Mon 30/3/20 162 1 165 1 179 1 Carriageway and Footway 496 days Mon 23/7/18 Mon 30/3/20 Design and Co-ordination for Road Lighting 76 days Mon 23/7/18 Wed 24/10/18 1171 days Fri 15/12/17 on 2 of the Works (Parts B1, B2, C, D, F, G1 & G2) Sat 27/2/21 180 Tree Survey and Report Submission 22 days Wed 28/2/18 Sat 24/3/18 Tree Felling and Tree Transplant 60 days Fri 4/5/18 Mon 16/7/18 21 days Thu 16/8/18 Sat 8/9/18 Erection of Site Hoarding 90 days Thu 16/8/18 Tue 4/12/18 Temporary Drainage Works 184 Enquiries of Utilities As-built Record from UU Companies 45 days Fri 15/12/17 Thu 8/2/18 185 **2** 186 **2** Uilities Detection and Reports Submission 45 days Fri 9/2/18 Tue 10/4/18 938 days Fri 15/12/17 Part B1 Sat 27/2/21 187 **2** Utilities Diversion/Protection Works 820 days Fri 15/12/17 Wed 30/9/20 820 days Fri 15/12/17 Wed 30/9/20 189 4 190 4 191 4 192 4 Liaison with HKT for Diversion/Supporting of Existing Cable 120 days Fri 15/12/17 Wed 16/5/18 12 days Thu 17/5/18 Trial Pits for HKT Cable Thu 31/5/18 Supporting / Diversion of Existing HKT Cable 700 days Thu 17/5/18 Wed 30/9/20 Ground Investigation and Geotechnical instrumentation for Commencement of Slopework 93 days Tue 20/3/18 Sat 14/7/18 Mobilization of GI Rig and Preparation Works 7 days Tue 20/3/18 Tue 27/3/18 Verification Drillholes (2 Nos. ,6, 14) and Preliminary Results Submission 12 days Wed 28/3/18 Sat 14/4/18 195 21 days Fri 4/5/18 Site Clerance for Verification Drillholes (8 Nos., VDH3.10-13, 15, 19 & 20) Tue 29/5/18 Verification Drillholes (8 Nos., VDH3,10-13, 15, 19 & 20) and Preliminary Results Submission 20 days Thu 10/5/18 Sat 2/6/18 Formal Report Submission and Verification of the Design of Cut and Fill Slope by PM 42 days Sun 3/6/18 Sat 14/7/18 20 days Mon 4/6/18 Geotechnical Instrumentation Required for Commencement of Slope Works Wed 27/6/18 434 days Sat 1/9/18 Temporary Excavation to Proposed Platform at Future PDA Wed 26/2/20 Excavate to +80 mPD 42 days Sat 1/9/18 Thu 25/10/18 86 days Fri 26/10/18 Excavate to +71 mPD Sat 9/2/19 663 days Sat 1/9/18 Cut Slopes CS11 & CS12 Sat 5/12/20 Mobilization of Plant and Equipment 12 days Sat 1/9/18 Fri 14/9/18 Excavate to +94 mPD 21 days Sat 15/9/18 Thu 11/10/18 Project: Master Programme Rev. 0c 20 Task ■ External Milestone ● Critical Milestone Project Summary Date: Sep 2018 Split Summary External Tasks Deadline Critical Split


Contract No. CV/2016/10 Hsin Chong Tsun Yip Joint Venture 3-month Rolling Programme (Oct 2018 to Dec 2018) Site Formation and Associated Infrastructural Works for Development of Columbarium at Sandy Ridge Cemetery 44 days Fri 12/10/18 Excavate to +87 mPD, Pull Out Test and Soil Nails (59 nos. of Soil Nail) Wed 5/12/18 223 Excavate to +79.5mPD, Pull Out Test, Soil Nails and Raking Drains (78 Nos. of Soil Nail) 63 days Thu 6/12/18 Sat 23/2/19 230 Drainage and Maintenance Access up to +72 mPD 235 days Tue 18/9/18 Fri 12/7/19 450 days Wed 31/10/18 Geotechnical Instrumentation Works Sat 16/5/20 Landscape Works at Cut Slopes CS11 & CS12 690 days Wed 10/10/18 Thu 18/2/21 238 days Wed 10/10/18 Planter W2 Construction Stage 1 up to +72 mPD Mon 5/8/19 240 **4** 249 **4** 212 days Tue 13/11/18 Hydroseeding Stage 1 up to +72 mPD Mon 5/8/19 Cut Slope CS13 696 days Fri 4/5/18 Sat 12/9/20 250 Trial Pit Excavation 50 days Fri 4/5/18 Wed 4/7/18 Verification of Design by Supervisor 42 days Thu 5/7/18 Wed 15/8/18 252 Excavate to +79.5mPD, Pull Out Test and Soil Nails (6 Nos. of Soil Nail) 63 days Thu 6/12/18 Sat 23/2/19 Drainage and Maintenance Access up to +72 mPD 235 days Tue 18/9/18 Fri 12/7/19 524 days Sat 1/9/18 Cut Slope CS15 Thu 18/6/20 Mobilization of Plant and Equipment 12 days Sat 1/9/18 Fri 14/9/18 Excavate to +69.5 mPD, Pull Out Test, Soil Nails and Raking Drains (25 nos. of Soil Nail) 27 days Sat 15/9/18 Mon 22/10/18 Excavate to +62mPD, Pull Out Test, Soil Nails and Raking Drains (76 nos. of Soil Nail, 31 nos. of 59 days Tue 23/10/18 Wed 2/1/19 Raking Drain) Geotechnical Instrumentation Works 460 days Tue 23/10/18 Wed 20/5/20 Cut Slopes CS16 and CS17 242 days Tue 23/10/18 Mon 19/8/19 289 Excavate to +62 mPD, Pull Out Test, Soil Nails and Raking Drains (23 Nos. of Soil Nail, 6 Nos. of 28 days Tue 23/10/18 Fri 23/11/18 Raking Drain) Drainage and Maintenance Access 207 days Fri 30/11/18 Fri 16/8/19 290 Geotechnical Instrumentation Works 180 days Fri 14/12/18 Tue 30/7/19 291 Fill Slope FS17 621 days Thu 5/7/18 Fri 14/8/20 Trial Pits Excavation and Preliminary Results Submission 25 days Thu 5/7/18 Thu 2/8/18 293 **4** 302 **4** 303 **6** Final Results Submission and Verification of Design by Supervisor 42 days Fri 3/8/18 Thu 13/9/18 Landscape Works at Cut Slopes CS16 and CS17 460 days Tue 3/7/18 Thu 23/1/20 Planter W2 Construction 196 days | Mon 24/12/18 Tue 27/8/19 307 4 376 3 387 4 388 4 413 4 360 days Tue 3/7/18 Fri 20/9/19 Hvdrosee di na 887 days Fri 15/12/17 Wed 23/12/20 602 days Sat 1/12/18 Sha Ling Road (M001 CH +40 to +180) Sat 19/12/20 TTA and XP Application for Existing Sha Ling Road 180 days Sat 1/12/18 Wed 17/7/19 836 days Fri 15/12/17 Wed 21/10/20 Man Kam To Road Bus Shelter 600 days Fri 15/12/17 Temporary Storage and Secondary Site Office Fri 3/1/20 749 days Fri 8/6/18 Sha Ling Road (M001 CH+0 to +40), Man Kam To Road Drainage, Sewerage, Watermains Wed 23/12/20 and Other Utilities 422 **4** 472 **4** TTA and XP Application at Man Kam To Road 270 days Fri 8/6/18 Sat 11/5/19 586 days Sat 15/12/18 Tue 15/12/20 473 586 days Sat 15/12/18 Woodland Planting Tue 15/12/20 495 **4** 496 **4** 642 days Fri 15/12/1 Temporary Drainage Works 90 days Thu 16/8/18 Tue 4/12/18 **Utilities Diversion/Protection Works** 30 days Fri 15/12/17 Mon 22/1/18 30 days Fri 15/12/17 Enquiries of As-built Record from UU Companies Mon 22/1/18 Ground Investigation and Geotechnical Instrumentation for Commencement of Slopework 50 days Fri 4/5/18 Wed 4/7/18 500 . 501 4 Site Clearance for Verification Drillholes (2 Nos., VDH4-5) 8 days Fri 4/5/18 Sat 12/5/18 Mobilization of GI Rig and Preparation of Works 7 days Fri 4/5/18 Fri 11/5/18 Verification Drillholes (2 Nos., VDH4-5) and Preliminary Results Submission Mon 14/5/18 8 days Wed 23/5/18 42 days Formal Report Submission and Verification of the Design of Cut and Fill Slope by PM Thu 24/5/18 Wed 4/7/18 Geotechnical Instrumentation Required for Commencement of Slope Works 12 days Thu 24/5/18 Wed 6/6/18 505 236 days Thu 16/8/18 Fill Slope FS3 Mon 10/6/19 Backfilling Stage 1 (~11m, up to +27 mPD at Section 17) 111 days Thu 16/8/18 Mon 31/12/18 Drainage, Maintenance Access after Backfilling Stage 1 94 days Tue 2/10/18 Fri 25/1/19 Project: Master Programme Rev. 0c 20 Task External Milestone Milestone Project Summary Critical Date: Sep 2018 External Tasks Deadline Critical Split Summary Page 2



Appendix D

Designated Monitoring Locations as Recommended in the Approved EM&A Manual


















CEDD No. Contract CV/2016/10 - Site Formation and Associated Infrastructural Works for Development of Columbarium at Sandy Ridge Cemetery Monthly Environmental Monitoring & Audit Report (No.3) – October 2018








Proposed Noise Monitoring Location under Contract 1



CEDD No. Contract CV/2016/10 - Site Formation and Associated Infrastructural Works for Development of Columbarium at Sandy Ridge Cemetery Monthly Environmental Monitoring & Audit Report (No.3) – October 2018



Proposed Water Quality Monitoring Station under Contract





Appendix E

Calibration Certificate of Monitoring Equipment and Laboratory Certificate

TSP SAMPLER CALIBRATION CALCULATION SPREADSHEET

Location: Sha Ling Village House No.6 Date of Calibration: 16-Aug-18

Location ID: ASR-1 Next Calibration Date: 16-Oct-18 Name and Model: TISCH HVS Model TE-5170 Technician: Ip Ka Hing

CONDITIONS

Sea Level Pressure (hPa) Temperature (°C)

1015.8

Corrected Pressure (mm Hg) Temperature (K)

761.85 296

CALIBRATION ORIFICE

Make-> TISCH Model-> 5025A Serial # -> 1612

Qstd Slope -> Qstd Intercept -> 2.02017 0.03691

CALIBRATION

Plate	H20 (L)	H2O (R)	H20	Qstd	Ι	IC	LINEAR
No.	(in)	(in)	(in)	(m3/min)	(chart)	corrected	REGRESSION
18	5.40	5.40	10.8	1.654	52	52.50	Slope = 43.0586
13	4.20	4.20	8.4	1.461	44	44.43	Intercept = -18.9634
10	3.40	3.40	6.8	1.316	37	37.36	Corr. coeff. = 0.9974
7	2.20	2.20	4.4	1.062	25	25.24	
5	1.35	1.35	2.7	0.836	18	18.17	

Calculations:

Qstd = 1/m[Sqrt(H20(Pa/Pstd)(Tstd/Ta))-b]

IC = I[Sqrt(Pa/Pstd)(Tstd/Ta)]

Ostd = standard flow rate

IC = corrected chart respones

I = actual chart response

m = calibrator Qstd slope

b = calibrator Qstd intercept

Ta = actual temperature during calibration (deg K)

Pstd = actual pressure during calibration (mm Hg

For subsequent calculation of sampler flow:

1/m((I)[Sqrt(298/Tav)(Pav/760)]-b)


m = sampler slope

b = sampler intercept

I = chart response

Tay = daily average temperature

Pav = daily average pressure



TSP SAMPLER CALIBRATION CALCULATION SPREADSHEET

Location: Sha Ling Village House No.6

Location ID: ASR-1

Date of Calibration: 16-Oct-18 Next Calibration Date: 16-Dec-18

Name and Model: TISCH HVS Model TE-5170 Technician: Ip Ka Hing

CONDITIONS

Sea Level Pressure (hPa) Temperature (°C) 1013.2 22.5 Corrected Pressure (mm Hg)
Temperature (K)

759.9 296

CALIBRATION ORIFICE

Make-> TISCH
Model-> 5025A
Serial # -> 1612

Qstd Slope -> Qstd Intercept ->

2.02017 -0.03691

CALIBRATION

P1	ate	H20 (L)	H2O (R)	H20	Qstd	Ι	IC	LINEAR
N	No.	(in)	(in)	(in)	(m3/min)	(chart)	corrected	REGRESSION
	18	2.00	7.80	9.8	1.574	49	49.41	Slope = 35.3099
	13	1.00	6.80	7.8	1.406	44	44.37	Intercept = -5.7176
	10	0.10	5.90	6.0	1.236	37	37.31	Corr. coeff. = 0.9937
	7	-1.20	4.80	3.6	0.961	30	30.25	
	5	-1.80	4.10	2.3	0.772	20	20.17	

Calculations:

Qstd = 1/m[Sqrt(H20(Pa/Pstd)(Tstd/Ta))-b]

IC = I[Sqrt(Pa/Pstd)(Tstd/Ta)]

Qstd = standard flow rate

IC = corrected chart respones

I = actual chart response

m = calibrator Qstd slope

b = calibrator Qstd intercept

Ta = actual temperature during calibration (deg K

Pstd = actual pressure during calibration (mm Hg

For subsequent calculation of sampler flow:

1/m((I)[Sqrt(298/Tav)(Pav/760)]-b)


m = sampler slope

b = sampler intercept

I = chart response

Tay = daily average temperature

Pav = daily average pressure





RECALIBRATION DUE DATE:

February 13, 2019

Certificate of Calibration

Calibration Certification Information

Cal. Date: February 13, 2018

Rootsmeter S/N: 438320

°K

Operator: Jim Tisch

Ta: 293 **Pa:** 763.3

mm Hg

Calibration Model #: TE-5025A

Calibrator S/N: 1612

Run	Vol. Init (m3)	Vol. Final (m3)	ΔVol. (m3)	ΔTime (min)	ΔP (mm Hg)	ΔH (in H2O)
1	1	2	1	1.3970	3.2	2.00
2	3	4	1	1.0000	6.3	4.00
3	5	6	1	0.8900	7.9	5.00
4	7	8	1	0.8440	8.7	5.50
5	9	10	1	0.7010	12.6	8.00

	Data Tabulation								
Vstd	Qstd	$\sqrt{\Delta H \left(\frac{Pa}{Pstd}\right) \left(\frac{Tstd}{Ta}\right)}$		Qa	$\sqrt{\Delta H \Big(Ta/Pa \Big)}$				
(m3)	(x-axis)	(y-axis)	Va	(x-axis)	(y-axis)				
1.0172	0.7281	1.4293	0.9958	0.7128	0.8762				
1.0130	1.0130	2.0213	0.9917	0.9917	1.2392				
1.0109	1.1358	2.2599	0.9896	1.1120	1.3854				
1.0098	1.1964	2.3702	0.9886	1.1713	1.4530				
1.0046	1.4331	2.8586	0.9835	1.4030	1.7524				
	m=	2.02017		m=	1.26500				
QSTD	b=	-0.03691	QA	b=	-0.02263				
	r=	0.99988		r=	0.99988				

Calculations						
Vstd=	ΔVoI((Pa-ΔP)/Pstd)(Tstd/Ta)	Va=	ΔVol((Pa-ΔP)/Pa)			
Qstd=	Vstd/ΔTime	Qa=	Va/ΔTime			
For subsequent flow rate calculations:						
Qstd=	$1/m\left(\left(\sqrt{\Delta H\left(\frac{Pa}{Pstd}\right)\left(\frac{Tstd}{Ta}\right)}\right)-b\right)$	Qa=	$1/m\left(\left(\sqrt{\Delta H\left(Ta/Pa\right)}\right)-b\right)$			

Standard Conditions						
Tstd: 298.15 °K						
Pstd:	760 mm Hg					
	Key					
	ΔH: calibrator manometer reading (in H2O)					
ΔP: rootsmeter manometer reading (mm Hg)						
Ta: actual absolute temperature (°K)						
Pa: actual barometric pressure (mm Hg)						
b: intercept						
m: slope						

RECALIBRATION

US EPA recommends annual recalibration per 1998 40 Code of Federal Regulations Part 50 to 51, Appendix B to Part 50, Reference Method for the Determination of Suspended Particulate Matter in the Atmosphere, 9.2.17, page 30

Tisch Environmental, Inc. 145 South Miami Avenue Village of Cleves, OH 45002 www.tisch-env.cor

TOLL FREE: (877)263-761(

FAX: (513)467-900

ALS Technichem (HK) Pty Ltd

ALS Laboratory Group





SUB-CONTRACTING REPORT

: MR BEN TAM CONTACT

WORK ORDER

HK1825892

CLIENT

ACTION UNITED ENVIRONMENT SERVICES AND

CONSULTING

RM A 20/F., GOLD KING IND BLDG, NO. 35-41 TAI LIN PAI ROAD, SUB-BATCH

KWAI CHUNG, N.T. HONG KONG

DATE RECEIVED DATE OF ISSUE

: 12-APR-2018 : 19-APR-2018

PROJECT

ADDRESS

NO. OF SAMPLES

: 1

CLIENT ORDER

General Comments

- Sample(s) were received in ambient condition.
- Sample(s) analysed and reported on an as received basis.
- Calibration was subcontracted to and analysed by Action United Enviro Services.

Signatories

This document has been signed by those names that appear on this report and are the authorised signatories

Signatories

Position

Richard Fung

General Manager



WORK ORDER

: HK1825892

SUB-BATCH

. .

CLIENT PROJECT : ACTION UNITED ENVIRONMENT SERVICES AND CONSULTING

: ---



ALS Lab	Client's Sample ID	Sample Type	Sample Date	External Lab Report No.
HK1825892-001	S/N: 456660	Equipments	12-Apr-2018	S/N: 456660

Equipment Verification Report (TSP)

Equipment Calibrated:

Type:

Laser Dust monitor

Manufacturer:

Sibata LD-3B

Serial No.

456660

Equipment Ref:

EQ117

Job Order

HK1825892

Standard Equipment:

Standard Equipment:

Higher Volume Sampler

Location & Location ID:

AUES office (calibration room)

Equipment Ref:

HVS 018

Last Calibration Date:

27 February 2018

Equipment Verification Results:

Calibration Date:

12 & 13 March 2018

Hour	Time	Mean Temp °C	Mean Pressure (hPa)	Concentration in mg/m³ (Standard Equipment)	Total Count (Calibrated Equipment)	Count/Minute (Total Count/60min)
2hr07min	9:50 ~ 11:57	19.6	1019.0	0.073	4016	31.7
2hr14min	12:05 ~ 14:19	19.6	1019.0	0.075	4544	33.8
2hr17min	9:50 ~ 12:07	20.9	1016.7	0.075	4912	35.7

Sensitivity Adjustment Scale Setting (Before Calibration)

615 (CPM) 615 (CPM)

Sensitivity Adjustment Scale Setting (After Calibration)

Linear Regression of Y or X

Slope (K-factor):

0.0022

Correlation Coefficient (R)

0.9970

Date of Issue

15 March 2018

Remarks:

- 1. Strong Correlation (R>0.8)
- Factor 0.0022 should be apply for TSP monitoring

*If R<0.5, repair or re-verification is required for the equipment

0.09 0.08 0.07 0.06 0.05 0.04 y = 0.0022x + 0.00040.03 $R^2 - 0.9941$ 0.02 0.01

Operator: Martin Li

Signature:

Date:

15 March 2018

QC Reviewer:

Ben Tam

Signature:

Date: <u>15 March 2018</u>

TSP SAMPLER CALIBRATION CALCULATION SPREADSHEET

Location:

Gold King Industrial Building, Kwai Chung

Location ID:

Calibration Room

Date of Calibration: 27-Feb-18

Next Calibration Date: 27-May-18

CONDITIONS

Sea Level Pressure (hPa) Temperature (°C) 1017.3 19.1

Corrected Pressure (mm Hg)
Temperature (K)

762.975 292

CALIBRATION ORIFICE

Make-> TISCH
Model-> 5025A
Calibration Date-> 28-Feb-17

Qstd Slope -> Qstd Intercept -> Expiry Date-> 2.11965 -0.02696 28-Feb-18

CALIBRATION

Plate	H20 (L)	H2O (R)	H20	Qstd	I	IC	LINEAR
No.	(in)	(in)	(in)	(m3/min)	(chart)	corrected	REGRESSION
18	6.2	6.2	12.4	1.694	52	52.63	Slope = 39.8525
13	5.1	5.1	10.2	1.538	46	46.55	Intercept = -14.3322
10	3.9	3.9	7.8	1.346	40	40.48	Corr. coeff. = 0.9974
8	2.6	2.6	5.2	1.101	30	30.36	
5	1.7	1.7	3.4	0.893	20	20.24	

Calculations:

Qstd = 1/m[Sqrt(H20(Pa/Pstd)(Tstd/Ta))-b]

IC = I[Sqrt(Pa/Pstd)(Tstd/Ta)]

Ostd = standard flow rate

IC = corrected chart respones

I = actual chart response

m = calibrator Qstd slope

b = calibrator Qstd intercept

Ta = actual temperature during calibration (deg K)

Pstd = actual pressure during calibration (mm Hg)

For subsequent calculation of sampler flow:

1/m((I)[Sqrt(298/Tav)(Pav/760)]-b)


m = sampler slope

b = sampler intercept

I = chart response

Tav = daily average temperature

Pav = daily average pressure





Sun Creation Engineering Limited

Calibration & Testing Laboratory

Certificate of Calibration 校正證書

Certificate No.:

C183085

證書編號

ITEM TESTED / 送檢項目 (Job No. / 序引編號: IC18-0867)

Date of Receipt / 收件日期: 28 May 2018

Description / 儀器名稱

Integrating Sound Level Meter (EQ006)

Manufacturer / 製造商

Brüel & Kjær

Model No. / 型號

2238

Serial No. / 編號

2285762

Supplied By / 委託者

Action-United Environmental Services and Consulting

Unit A, 20/F., Gold King Industrial Building, 35-41 Tai Lin Pai Road, Kwai Chung, N.T.

TEST CONDITIONS / 測試條件

Temperature / 温度 :

 $(23 \pm 2)^{\circ}$ C

Relative Humidity / 相對濕度 :

 $(50 \pm 25)\%$

Line Voltage / 電壓 :

TEST SPECIFICATIONS / 測試規範

Calibration check

DATE OF TEST / 測試日期

10 June 2018

TEST RESULTS / 測試結果

The results apply to the particular unit-under-test only.

The results do not exceed manufacturer's specification.

The results are detailed in the subsequent page(s).

The test equipment used for calibration are traceable to National Standards via:

- The Government of The Hong Kong Special Administrative Region Standard & Calibration Laboratory
- Agilent Technologies / Keysight Technologies
- Rohde & Schwarz Laboratory, Germany
- Fluke Everett Service Center, USA

Tested By 測試

K C Lee Engineer

Certified By 核證

H C Chan

Date of Issue 簽發日期

11 June 2018

Engineer

The test equipment used for calibration are traceable to the Nation Standards as specified in this certificate. This certificate shall not be reproduced except in full, without the prior written approval of this laboratory

本證書所載校正用之測試器材均可溯源至國際標準。局部複印本證書需先獲本實驗所書面批准。



Sun Creation Engineering Limited

Calibration & Testing Laboratory

Certificate of Calibration 校正證書

Certificate No.: C183085

證書編號

The unit-under-test (UUT) was allowed to stabilize in the laboratory for over 12 hours, and switched on to 1. warm up for over 10 minutes before the commencement of the test.

- 2. Self-calibration using laboratory acoustic calibrator was performed before the test from 6.1.1.2 to 6.4.
- 3. The results presented are the mean of 3 measurements at each calibration point.
- 4. Test equipment:

Equipment ID

Description

Certificate No.

CL280 CL281

40 MHz Arbitrary Waveform Generator Multifunction Acoustic Calibrator

C180024

PA160023

- 5. Test procedure: MA101N.
- 6. Results:
- 6.1 Sound Pressure Level
- 6.1.1 Reference Sound Pressure Level

6.1.1.1 Before Self-calibration

UUT Setting				Applied	Value	UUT
Range	Parameter	Frequency	Time	Level	Freq.	Reading
(dB)		Weighting	Weighting	(dB)	(kHz)	(dB)
52 - 132	L_{AFP}	A	F	94.00	1	94.1

6.1.1.2 After Self-calibration

	UUT Setting				Applied Value		IEC 60651
Range	Parameter	Frequency	Time	Level	Freq.	Reading	Type 1 Spec.
(dB)		Weighting	Weighting	(dB)	(kHz)	(dB)	(dB)
52 - 132	L_{AFP}	A	F	94.00	1	94.0	± 0.7

6.1.2 Linearity

	UU	Γ Setting	Applied	d Value	UUT	
Range	Parameter	Frequency	Time	Level	Freq.	Reading
(dB)		Weighting	Weighting	(dB)	(kHz)	(dB)
52 - 132	L_{AFP}	A	F	94.00	1	94.0 (Ref.)
				104.00		104.0
				114.00		114.0

IEC 60651 Type 1 Spec. : \pm 0.4 dB per 10 dB step and \pm 0.7 dB for overall different.

The test equipment used for calibration are traceable to the Nation Standards as specified in this certificate. This certificate shall not be reproduced except in full, without the prior written approval of this laboratory

本證書所載校正用之測試器材均可溯源至國際標準。局部複印本證書需先獲本實驗所書面批准。

Sun Creation Engineering Limited - Calibration & Testing Laboratory c/o 4/F, 1 Hing On Lane, Tuen Mun, New Territories, Hong Kong 輝創工程有限公司 — 校正及檢測實驗所



Sun Creation Engineering Limited

Calibration & Testing Laboratory

Certificate of Calibration 校正證書

Certificate No.: C183085

證書編號

6.2 Time Weighting

6.2.1 Continuous Signal

	UUT Setting				d Value	UUT	IEC 60651
Range	Parameter	Frequency	Time	Level	Freq.	Reading	Type 1 Spec.
(dB)		Weighting	Weighting	(dB)	(kHz)	(dB)	(dB)
52 - 132	L_{AFP}	A	F	94.00	1	94.0	Ref.
	L_{ASP}		S			94.0	± 0.1
	L_{AIP}		I			94.1	± 0.1

6.2.2 Tone Burst Signal (2 kHz)

	UUT	Setting		Applied Value		UUT	IEC 60651
Range	Parameter	Frequency	Time	Level	Burst	Reading	Type 1 Spec.
(dB)		Weighting	Weighting	(dB)	Duration	(dB)	(dB)
32 - 112	L_{AFP}	A	F	106.0	Continuous	106.0	Ref.
	L_{AFMax}				200 ms	104.9	-1.0 ± 1.0
	L_{ASP}		S		Continuous	106.0	Ref.
	L _{ASMax}				500 ms	102.0	-4.1 ± 1.0

6.3 Frequency Weighting

6.3.1 A-Weighting

	UUT	Setting		Appli	ed Value	UUT	IEC 60651
Range	Parameter	Frequency	Time	Level	Freq.	Reading	Type 1 Spec.
(dB)		Weighting	Weighting	(dB)		(dB)	(dB)
52 - 132	L_{AFP}	A	F	94.00	31.5 Hz	55.0	-39.4 ± 1.5
					63 Hz	67.9	-26.2 ± 1.5
					125 Hz	77.8	-16.1 ± 1.0
					250 Hz	85.3	-8.6 ± 1.0
					500 Hz	90.7	-3.2 ± 1.0
					1 kHz	94.0	Ref.
					2 kHz	95.2	$+1.2 \pm 1.0$
					4 kHz	95.0	$+1.0 \pm 1.0$
					8 kHz	92.9	-1.1 (+1.5; -3.0)
					12.5 kHz	89.8	-4.3 (+3.0 ; -6.0)

The test equipment used for calibration are traceable to the Nation Standards as specified in this certificate. This certificate shall not be reproduced except in full, without the prior written approval of this laboratory

本證書所載校正用之測試器材均可溯源至國際標準。局部複印本證書需先獲本實驗所書面批准。

Sun Creation Engineering Limited - Calibration & Testing Laboratory c/o 4/F, 1 Hing On Lane, Tuen Mun, New Territories, Hong Kong 輝創工程有限公司 — 校正及檢測實驗所



Sun Creation Engineering Limited

Calibration & Testing Laboratory

Certificate of Calibration

校正證書

Certificate No.:

C183085

證書編號

6.3.2 C-Weighting

	UUT	Setting		Applied Value		UUT	IEC 60651
Range	Parameter	Frequency	Time	Level	Freq.	Reading	Type 1 Spec.
(dB)		Weighting	Weighting	(dB)	•	(dB)	(dB)
52 - 132	L_{CFP}	C	F	94.00	31.5 Hz	91.4	-3.0 ± 1.5
					63 Hz	93.3	-0.8 ± 1.5
					125 Hz	93.8	-0.2 ± 1.0
					250 Hz	94.0	0.0 ± 1.0
					500 Hz	94.0	0.0 ± 1.0
					1 kHz	94.0	Ref.
					2 kHz	93.8	-0.2 ± 1.0
					4 kHz	93.2	-0.8 ± 1.0
					8 kHz	90.9	-3.0 (+1.5; -3.0)
					12.5 kHz	87.8	-6.2 (+3.0 ; -6.0)

6.4 Time Averaging

	UUT Setting				Applied Value					IEC 60804
Range	Parameter	Frequency	Integrating	Frequency	Burst	Burst	Burst	Equivalent	Reading	Type 1
(dB)		Weighting	Time	(kHz)	Duration	Duty	Level	Level	(dB)	Spec.
					(ms)	Factor	(dB)	(dB)		(dB)
32 - 112	L_{Aeq}	A	10 sec.	4	1	1/10	110.0	100	100.0	± 0.5
						$1/10^{2}$		90	89.5	± 0.5
			60 sec.			$1/10^{3}$		80	79.2	± 1.0
			5 min.			1/104		70	69.3	± 1.0

Remarks: - UUT Microphone Model No.: 4188 & S/N: 2812706

- Mfr's Spec. : IEC 60651 Type 1 & IEC 60804 Type 1

- Uncertainties of Applied Value : 94 dB : 31.5 Hz - 125 Hz : $\pm 0.35 \text{ dB}$

250 Hz - 500 Hz : \pm 0.30 dB 1 kHz $: \pm 0.20 \text{ dB}$ 2 kHz - 4 kHz $: \pm 0.35 \text{ dB}$ 8 kHz $: \pm 0.45 \text{ dB}$ 12.5 kHz $: \pm 0.70 \text{ dB}$

104 dB : 1 kHz 114 dB : 1 kHz Burst equivalent level $: \pm 0.10 \text{ dB (Ref. 94 dB)}$

 $: \pm 0.10 \text{ dB (Ref. 94 dB)}$ $: \pm 0.2 \text{ dB (Ref. 110 dB)}$ continuous sound level)

- The uncertainties are for a confidence probability of not less than 95 %.

Note:

Only the original copy or the laboratory's certified true copy is valid.

The values given in this Certificate only relate to the values measured at the time of the test and any uncertainties quoted will not include allowance for the equipment long term drift, variations with environment changes, vibration and shock during transportation, overloading, mis-handling, or the capability of any other laboratory to repeat the measurement. Sun Creation Engineering Limited shall not be liable for any loss or damage resulting from the use of the equipment.

The test equipment used for calibration are traceable to the Nation Standards as specified in this certificate. This certificate shall not be reproduced except in full, without the prior written approval of this laboratory.

本證書所載校正用之測試器材均可溯源至國際標準。局部複印本證書需先獲本實驗所書面批准。



Sun Creation Engineering Limited

Calibration & Testing Laboratory

Certificate of Calibration 校正證書

Certificate No.: C183082

證書編號

ITEM TESTED / 送檢項目 (Job No. / 序引編號: IC18-0867)

Date of Receipt / 收件日期: 28 May 2018

Description / 儀器名稱

Acoustical Calibrator (EQ081)

Manufacturer / 製造商

Brüel & Kjær

Model No. / 型號

4231

Serial No. / 編號 Supplied By / 委託者 2326408 Action-United Environmental Services and Consulting

Unit A, 20/F., Gold King Industrial Building, 35-41 Tai Lin Pai Road, Kwai Chung, N.T.

TEST CONDITIONS / 測試條件

Temperature / 温度 :

 $(23 \pm 2)^{\circ}$ C

Relative Humidity / 相對濕度 :

Line Voltage / 電壓 :

TEST SPECIFICATIONS / 測試規節

Calibration check

DATE OF TEST / 測試日期

9 June 2018

TEST RESULTS / 測試結果

The results apply to the particular unit-under-test only.

The results do not exceed manufacturer's specification.

The results are detailed in the subsequent page(s).

The test equipment used for calibration are traceable to National Standards via:

- The Government of The Hong Kong Special Administrative Region Standard & Calibration Laboratory
- Agilent Technologies / Keysight Technologies
- Rohde & Schwarz Laboratory, Germany
- Fluke Everett Service Center, USA

Tested By 測試

K 🕻 Lee Engineer

Certified By 核證

H C Chan

Date of Issue

11 June 2018

Engineer

The test equipment used for calibration are traceable to the Nation Standards as specified in this certificate. This certificate shall not be reproduced except in full, without the prior written approval of this laboratory

本證書所載校正用之測試器材均可溯源至國際標準。局部複印本證書需先獲本實驗所書面批准。

Sun Creation Engineering Limited - Calibration & Testing Laboratory c/o 4/F, 1 Hing On Lane, Tuen Mun, New Territories, Hong Kong 輝創工程有限公司 — 校正及檢測實驗所

c/o 香港新界屯門興安里一號四樓

Tel/電話: (852) 2927 2606 Fax/傳真: (852) 2744 8986 E-mail/電郵: callab@suncreation.com

Website/網址: www.suncreation.com

Certificate of Calibration 校正證書

Certificate No.: C183082

證書編號

1. The unit-under-test (UUT) was allowed to stabilize in the laboratory for over 12 hours before the commencement of the test.

2. The results presented are the mean of 3 measurements at each calibration point.

3. Test equipment:

Equipment ID

CL130

CL281 TST150A **Description**

Universal Counter

Multifunction Acoustic Calibrator

Measuring Amplifier

Certificate No.

C173864 PA160023

C181288

4. Test procedure: MA100N.

5. Results:

5.1 Sound Level Accuracy

UUT	Measured Value	Mfr's Spec.	Uncertainty of Measured Value
Nominal Value	(dB)	(dB)	(dB)
94 dB, 1 kHz	94.0	± 0.2	± 0.2
114 dB, 1 kHz	114.0		

5.2 Frequency Accuracy

UUT Nominal Value	Measured Value	Mfr's	Uncertainty of Measured Value
(kHz)	(kHz)	Spec.	(Hz)
1	1.000 0	$1 \text{ kHz} \pm 0.1 \%$	± 0.1

Remark: The uncertainties are for a confidence probability of not less than 95 %.

Note:

Only the original copy or the laboratory's certified true copy is valid.

The values given in this Certificate only relate to the values measured at the time of the test and any uncertainties quoted will not include allowance for the equipment long term drift, variations with environment changes, vibration and shock during transportation, overloading, mis-handling, or the capability of any other laboratory to repeat the measurement. Sun Creation Engineering Limited shall not be liable for any loss or damage resulting from the use of the equipment.

The test equipment used for calibration are traceable to the Nation Standards as specified in this certificate. This certificate shall not be reproduced except in full, without the prior written approval of this laboratory.

本證書所載校正用之測試器材均可溯源至國際標準。局部複印本證書需先獲本實驗所書面批准。

Sun Creation Engineering Limited – Calibration & Testing Laboratory c/o 4/F, 1 Hing On Lane, Tuen Mun, New Territories, Hong Kong 輝創工程有限公司 — 校正及檢測實驗所 c/o 香港新界屯門興安里一號四樓



ALS Technichem (HK) Pty Ltd

11/F, Chung Shun Knitting Centre 1-3 Wing Yip Street, Kwai Chung N.T., Hong Kong

T: +852 2610 1044 | F: +852 2610 2021

REPORT OF EQUIPMENT PERFORMANCE CHECK/CALIBRATION

CONTACT: HK1840311 MR BEN TAM WORK ORDER:

CLIENT: ACTION UNITED ENVIRONMENT SERVICES AND

CONSULTING

RM A 20/F., GOLD KING IND BLDG, ADDRESS: SUB-BATCH:

> NO. 35-41 TAI LIN PAI ROAD, LABORATORY: HONG KONG KWAI CHUNG. DATE RECEIVED: 20-Jul-2018 N.T., HONG KONG. DATE OF ISSUE: 25-Jul-2018

COMMENTS

The performance of the equipment stated in this report is checked with independent reference material and results compared against a calibrated secondary source.

The "Tolerance Limit" quoted is the acceptance criteria applicable for similar equipment used by the ALS Hong Kong laboratory or quoted from relevant international standards.

The "Next Calibration Date" is recommended according to best practice principle as practised by the ALS Hong Kong laboratory or quoted from relevant international standards.

Dissolved Oxygen and Temperature Scope of Test:

Equipment Type: Dissolved Oxygen Meter

Brand Name: YSI Pro 20 Model No.: Serial No.: 12C100570

Equipment No.:

Date of Calibration: 25 July, 2018

NOTES

This is the Final Report and supersedes any preliminary report with this batch number.

Results apply to sample(s) as submitted. All pages of this report have been checked and approved for release.

Mr Chan Siu Ming, Vico Manager - Inorganic

Ma Six

This report may not be reproduced except with prior written approval from ALS Technichem (HK) Pty Ltd.

REPORT OF EQUIPMENT PERFORMANCE CHECK/CALIBRATION

WORK ORDER: HK1840311

SUB-BATCH: 0

DATE OF ISSUE: 25-Jul-2018

CLIENT: ACTION UNITED ENVIRONMENT SERVICES AND CONSULTING

Equipment Type: Dissolved Oxygen Meter

Brand Name: YSI
Model No.: Pro 20
Serial No.: 12C100570

Equipment No.: --

Date of Calibration: 25 July, 2018 Date of Next Calibration: 25 October, 2018

PARAMETERS:

Dissolved Oxygen Method Ref: APHA (21st edition), 4500-O: G

Expected Reading (mg/L)	Displayed Reading (mg/L)	Tolerance (mg/L)
2.28	2.46	+0.18
4.90	4.77	-0.13
7.73	7.67	-0.06
	Tolerance Limit (mg/L)	±0.20

Temperature Method Ref: Section 6 of International Accreditation New Zealand Technical

Guide No. 3 Second edition March 2008: Working Thermometer Calibration Procedure.

Expected Reading (°C)	Displayed Reading (°C)	Tolerance (°C)
10.5	11.6	+1.1
21.0	22.7	+ 1.7
41.0	40.1	-0.9
	Tolerance Limit (°C)	±2.0

Remark: "Displayed Reading" presents the figures shown on item under calibration / checking regardless

of equipment precision or significant figures.

Mr Chan Siu Ming, Vico Manager - Inorganic

Ma Sig



ALS Technichem (HK) Pty Ltd

11/F, Chung Shun Knitting Centre 1-3 Wing Yip Street, Kwai Chung N.T., Hong Kong T: +852 2610 1044 | F: +852 2610 2021

REPORT OF EQUIPMENT PERFORMANCE CHECK/CALIBRATION

CONTACT: MR BEN TAM WORK ORDER: HK1853068

CLIENT: ACTION UNITED ENVIRONMENT SERVICES AND

CONSULTING

ADDRESS: RM A 20/F., GOLD KING IND BLDG, SUB-BATCH: (

NO. 35-41 TAI LIN PAI ROAD, LABORATORY: HONG KONG KWAI CHUNG, DATE RECEIVED: 05-Oct-2018 N.T., HONG KONG. DATE OF ISSUE: 11-Oct-2018

COMMENTS

The performance of the equipment stated in this report is checked with independent reference material and results compared against a calibrated secondary source.

The "Tolerance Limit" quoted is the acceptance criteria applicable for similar equipment used by the ALS Hong Kong laboratory or quoted from relevant international standards.

The "Next Calibration Date" is recommended according to best practice principle as practised by the ALS Hong Kong laboratory or quoted from relevant international standards.

Scope of Test: Dissolved Oxygen and Temperature

Equipment Type: Dissolved Oxygen Meter

Brand Name: YSI Model No.: 550A

Serial No.: 16A104433

Equipment No.:

Date of Calibration: 11 October, 2018

NOTES

This is the Final Report and supersedes any preliminary report with this batch number.

Results apply to sample(s) as submitted. All pages of this report have been checked and approved for release.

Mr Chan Siu Ming, Vico Manager - Inorganic

Ma Shi

 $This\ report\ may\ not\ be\ reproduced\ except\ with\ prior\ written\ approval\ from\ ALS\ Technichem\ (HK)\ Pty\ Ltd.$

REPORT OF EQUIPMENT PERFORMANCE CHECK/CALIBRATION

WORK ORDER: HK1853068

SUB-BATCH: 0

DATE OF ISSUE: 11-Oct-2018

CLIENT: ACTION UNITED ENVIRONMENT SERVICES AND CONSULTING

Equipment Type: Dissolved Oxygen Meter

Brand Name: YSI Model No.: 550A

Serial No.: 16A104433

Equipment No.: --

Date of Calibration: 11 October, 2018 Date of Next Calibration: 11 January, 2019

PARAMETERS:

Dissolved Oxygen Method Ref: APHA (21st edition), 4500-O: G

Expected Reading (mg/L)	Displayed Reading (mg/L)	Tolerance (mg/L)
2.87	3.01	+0.14
5.23	5.16	-0.07
7.85	7.96	+0.11
	Tolerance Limit (mg/L)	±0.20

Temperature Method Ref: Section 6 of International Accreditation New Zealand Technical

Guide No. 3 Second edition March 2008: Working Thermometer Calibration Procedure.

Expected Reading (°C)	Displayed Reading (°C)	Tolerance (°C)
9.0	10.8	+1.8
20.0	19.9	-0.1
38.5	37.4	-1.1
	Tolerance Limit (°C)	±2.0

Remark: "Displayed Reading" presents the figures shown on item under calibration / checking regardless of equipment precision or significant figures.

Ma Sig

Mr Chan Siu Ming, Vico Manager - Inorganic



ALS Technichem (HK) Pty Ltd

11/F, Chung Shun Knitting Centre 1-3 Wing Yip Street, Kwai Chung N.T., Hong Kong

T: +852 2610 1044 | F: +852 2610 2021

REPORT OF EQUIPMENT PERFORMANCE CHECK/CALIBRATION

CONTACT: HK1846347 MR BEN TAM WORK ORDER:

CLIENT: ACTION UNITED ENVIRONMENT SERVICES AND

CONSULTING

RM A 20/F., GOLD KING IND BLDG, ADDRESS: SUB-BATCH:

> NO. 35-41 TAI LIN PAI ROAD, HONG KONG LABORATORY: KWAI CHUNG. DATE RECEIVED: 27-Aug-2018 N.T., HONG KONG. DATE OF ISSUE: 04-Sep-2018

COMMENTS

The performance of the equipment stated in this report is checked with independent reference material and results compared against a calibrated secondary source.

The "Tolerance Limit" quoted is the acceptance criteria applicable for similar equipment used by the ALS Hong Kong laboratory or quoted from relevant international standards.

The "Next Calibration Date" is recommended according to best practice principle as practised by the ALS Hong Kong laboratory or quoted from relevant international standards.

Turbidity Scope of Test:

Turbidimeter Equipment Type:

Brand Name: Hach Model No.: 2100Q

11030C008499 Serial No.:

Equipment No.:

Date of Calibration: 30 August, 2018

NOTES

This is the Final Report and supersedes any preliminary report with this batch number.

Results apply to sample(s) as submitted. All pages of this report have been checked and approved for release.

Mr Chan Siu Ming, Vico Manager - Inorganic

Ma Shi

This report may not be reproduced except with prior written approval from ALS Technichem (HK) Pty Ltd.

REPORT OF EQUIPMENT PERFORMANCE CHECK/CALIBRATION

WORK ORDER: HK1846347

SUB-BATCH: 0

DATE OF ISSUE: 04-Sep-2018

CLIENT: ACTION UNITED ENVIRONMENT SERVICES AND CONSULTING

Equipment Type: Turbidimeter

Brand Name: Hach Model No.: 2100Q

Serial No.: 11030C008499

Equipment No.: --

Date of Calibration: 30 August, 2018 Date of Next Calibration: 30 November, 2018

PARAMETERS:

Turbidity Method Ref: APHA (21st edition), 2130B

Expected Reading (NTU)	Displayed Reading (NTU)	Tolerance (%)
0	0.17	- -
4		N/A
40	41.10	+2.8
80	84.8	+6.0
400	383	-4.3
800	790	-1.3
	Tolerance Limit (%)	±10.0

Remark: "Displayed Reading" presents the figures shown on item under calibration / checking regardless of equipment precision or significant figures.

Mr Chan Siu Ming, Vico Manager - Inorganic

Ma Ship



ALS Technichem (HK) Pty Ltd

11/F, Chung Shun Knitting Centre 1-3 Wing Yip Street, Kwai Chung N.T., Hong Kong T: +852 2610 1044 | F: +852 2610 2021

REPORT OF EQUIPMENT PERFORMANCE CHECK/CALIBRATION

CONTACT: MR BEN TAM WORK ORDER: HK1846345

CLIENT: ACTION UNITED ENVIRONMENT SERVICES AND

CONSULTING

ADDRESS: RM A 20/F., GOLD KING IND BLDG, SUB-BATCH: C

NO. 35-41 TAI LIN PAI ROAD,

KWAI CHUNG,

N.T., HONG KONG.

LABORATORY: HONG KONG

27-Aug-2018

DATE OF ISSUE: 03-Sep-2018

COMMENTS

The performance of the equipment stated in this report is checked with independent reference material and results compared against a calibrated secondary source.

The "Tolerance Limit" quoted is the acceptance criteria applicable for similar equipment used by the ALS Hong Kong laboratory or quoted from relevant international standards.

The "Next Calibration Date" is recommended according to best practice principle as practised by the ALS Hong Kong laboratory or quoted from relevant international standards.

Scope of Test: pH Value and Temperature

Equipment Type: pH meter

Brand Name: AZ Model No.: 8685 Serial No.: 1118396

Equipment No.: --

Date of Calibration: 30 August, 2018

NOTES

This is the Final Report and supersedes any preliminary report with this batch number.

Results apply to sample(s) as submitted. All pages of this report have been checked and approved for release.

Ms. Lin Wai Yu

Assistant Manager - Inorganic

 $This\ report\ may\ not\ be\ reproduced\ except\ with\ prior\ written\ approval\ from\ ALS\ Technichem\ (HK)\ Pty\ Ltd.$

REPORT OF EQUIPMENT PERFORMANCE CHECK/CALIBRATION

WORK ORDER: HK1846345

SUB-BATCH: 0

DATE OF ISSUE: 03-Sep-2018

CLIENT: ACTION UNITED ENVIRONMENT SERVICES AND CONSULTING

Equipment Type: pH meter

Brand Name: AZ
Model No.: 8685
Serial No.: 1118396

Equipment No.: --

Date of Calibration: 30 August, 2018 Date of Next Calibration: 30 November, 2018

PARAMETERS:

pH Value Method Ref: APHA (21st edition), 4500H:B

,		
Expected Reading (pH unit)	Displayed Reading (pH unit)	Tolerance (pH unit)
4.0	4.0	+0.00
7.0	7.0	+0.00
10.0	9.8	-0.20
	Tolerance Limit (pH unit)	±0.20

Temperature Method Ref: Section 6 of International Accreditation New Zealand Technical

Guide No. 3 Second edition March 2008: Working Thermometer Calibration Procedure.

	9	
Expected Reading (°C)	Displayed Reading (°C)	Tolerance (°C)
11.0	11.5	+0.5
22.0	22.0	+0.0
38.5	37.5	-1.0
	Tolerance Limit (°C)	±2.0

Remark: "Displayed Reading" presents the figures shown on item under calibration / checking regardless of equipment precision or significant figures.

Ms. Lin Wai Yu

Assistant Manager - Inorganic



ALS Technichem (HK) Pty Ltd

11/F, Chung Shun Knitting Centre 1-3 Wing Yip Street, Kwai Chung N.T., Hong Kong

T: +852 2610 1044 | F: +852 2610 2021

REPORT OF EQUIPMENT PERFORMANCE CHECK/CALIBRATION

CONTACT: MR BEN TAM HK1845007 WORK ORDER:

CLIENT: ACTION UNITED ENVIRONMENT SERVICES AND

CONSULTING

RM A 20/F., GOLD KING IND BLDG, ADDRESS: SUB-BATCH:

> NO. 35-41 TAI LIN PAI ROAD, HONG KONG LABORATORY: KWAI CHUNG, DATE RECEIVED: 17-Aug-2018 N.T., HONG KONG. DATE OF ISSUE: 24-Aug-2018

COMMENTS

The performance of the equipment stated in this report is checked with independent reference material and results compared against a calibrated secondary source.

The "Tolerance Limit" quoted is the acceptance criteria applicable for similar equipment used by the ALS Hong Kong laboratory or quoted from relevant international standards.

The "Next Calibration Date" is recommended according to best practice principle as practised by the ALS Hong Kong laboratory or quoted from relevant international standards.

Scope of Test: Salinity

Equipment Type: Salinity Meter

Brand Name:

Model No.: AZ8371 Serial No.: 1118267

Equipment No.:

Date of Calibration: 22 August, 2018

NOTES

This is the Final Report and supersedes any preliminary report with this batch number.

Results apply to sample(s) as submitted. All pages of this report have been checked and approved for release.

Ms. Lin Wai Yu

Assistant Manager - Inorganic

This report may not be reproduced except with prior written approval from ALS Technichem (HK) Pty Ltd.

REPORT OF EQUIPMENT PERFORMANCE CHECK/CALIBRATION

WORK ORDER: HK1845007

SUB-BATCH: 0

DATE OF ISSUE: 24-Aug-2018

CLIENT: ACTION UNITED ENVIRONMENT SERVICES AND CONSULTING

Equipment Type: Salinity Meter

Brand Name: --

Model No.: AZ8371 Serial No.: 1118267

Equipment No.: --

Date of Calibration: 22 August, 2018 Date of Next Calibration: 22 November, 2018

PARAMETERS:

Salinity Method Ref: APHA (21st edition), 2520B

Expected Reading (ppt)	Displayed Reading (ppt)	Tolerance (%)
0	0.00	
10	9.31	-6.9
20	18.2	-9.0
30	28.3	-5.7
	Tolerance Limit (%)	±10.0

Remark: "Displayed Reading" presents the figures shown on item under calibration / checking regardless of equipment precision or significant figures.

Ms. Lin Wai Yu

Assistant Manager - Inorganic



ALS Technichem (HK) Pty Ltd

11/F, Chung Shun Knitting Centre 1-3 Wing Yip Street, Kwai Chung N.T., Hong Kong

T: +852 2610 1044 | F: +852 2610 2021

REPORT OF EQUIPMENT PERFORMANCE CHECK/CALIBRATION

CONTACT:

MR IVAN LEUNG

CLIENT:

ALS TECHNICHEM (HK) PTY LTD

ADDRESS:

11/F, CHUNG SHUN KNITTING CENTRE,

1-3 WING YIP STREET,

KWAI CHUNG,

N.T., HONG KONG

WORK ORDER: HK1827786

SUB-BATCH:

LABORATORY: DATE RECEIVED:

HONG KONG

DATE OF ISSUE:

06-Apr-2018 02-May-2018

COMMENTS

The calibration of flow rate performed by AUES staff on 6 April 2018.

Scope of Test:

Flow rate

Equipment Type:

Flow Meter

Brand Name:

Global Water

Model No.: Serial No.:

FP211

1449006330

Equipment No.:

Calibration Factor:

314

Date of Calibration: 06 April, 2018

NOTES

This is the Final Report and supersedes any preliminary report with this batch number. Results apply to sample(s) as submitted. All pages of this report have been checked and approved for release.

Mr. Fung Lim Chee, Richard

General Manager

Greater China & Hong Kong

This report may not be reproduced except with prior written approval from ALS Technichem (HK) Pty Ltd.

Page 1 of 2

REPORT OF EQUIPMENT PERFORMANCE CHECK/CALIBRATION



Work Order:

HK1827786

Sub-batch:

Date of Issue:

02-May-2018

Client:

ALS TECHNICHEM (HK) PTY LTD

Equipment Type:

Flow Meter

Brand Name:

Global Water

Model No.:

FP211

Serial No.:

1449006330

Equipment No.:

Calibration Factor:

314

Date of Calibration:

06 April, 2018

Parameters:

The calibration of flow meter is verified with another standard flow meter (SonTek IQ Standard Serial Number: IQ1217004) on site by AUES Staff.

Flow rate

Test	Standard Equipment Reading (m/s)	Verification Equipment Reading (m/s)	
1 st	0.12	0.1	
2 nd	0.12	0.1	
-	0.21	0.2	
3 rd	0.18	0.2	
4 th	0.49	0.5	
5 th	1.03	1.0	
6 th	0.97	1.0	

Mr. Fung Lim Chee Richard

General Manager -

Greater China & Hong Kong



Hong Kong Accreditation Service 香港認可處

Certificate of Accreditation

認可證書

This is to certify that 特此證明

ALS TECHNICHEM (HK) PTY LIMITED

11/F., Chung Shun Knitting Centre, 1-3 Wing Yip Street, Kwai Chung, New Territories, Hong Kong 香港新界葵涌永業街1-3號忠信針織中心11樓

has been accepted by the HKAS Executive, on the recommendation of the Accreditation Advisory Board, as a 為香港認可處執行機關根據認可諮詢委員會建議而接受的

HOKLAS Accredited Laboratory

「香港實驗所認可計劃」認可實驗所

This laboratory meets the requirements of ISO / IEC 17025: 2005 - General requirements for the competence 此實驗所符合ISO / IEC 17025: 2005 -《測試及校正實驗所能力的通用規定》所訂的要求, of testing and calibration laboratories and it has been accredited for performing specific tests or calibrations as 獲認可進行載於香港實驗所認可計劃《認可實驗所名冊》內下述測試類別中的指定 listed in the HOKLAS Directory of Accredited Laboratories within the test category of 測試或校正工作

Environmental Testing

環境測試

This laboratory is accredited in accordance with the recognised International Standard ISO / IEC 17025: 2005. 本實驗所乃根據公認的國際標準 ISO / IEC 17025 : 2005 獲得認可。 This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory 這項認可資格演示在指定範疇所需的技術能力及實驗所質量管理體系的運作 quality management system (see joint IAF-ILAC-ISO Communiqué). (見國際認可論壇、國際實驗所認可合作組織及國際標準化組織的聯合公報)。

The common seal of the Hong Kong Accreditation Service is affixed hereto by the authority of the HKAS Executive 香港認可處根據認可處執行機關的權限在此蓋上通用印章

CHAN Sing Sing, Terence, Executive Administrator

執行幹事 陳成城 Issue Date: 5 May 2009

簽發日期:二零零九年五月五日

註冊號碼:

Registration Number : HOKLAS 066

Date of First Registration: 15 September 1995 首次註冊日期:一九九五年九月十五日



Appendix F

Event and Action Plan of Air Quality, Noise and Water Quality



Event and Action Plan for air quality

F 4	Action			
Event	ET	IEC	ER	Contractor
Action level exceedance for one sample	1. Identify source, investigate the causes of exceedance and propose remedial measures; 2. Inform IEC and ER; 3. Repeat measurement to confirm finding; 4. Increase monitoring frequency to daily.	Check monitoring data submitted by ET; Check Contractor's working method.	1. Notify Contractor	 Rectify any unacceptable practice; Amend working methods if appropriate.
Action level exceedance for two or more consecutive samples	1. Identify source; 2. Inform IEC and ER; 3. Advise the ER on the effectiveness of the proposed remedial measures; 4. Repeat measurements to confirm findings; 5. Increase monitoring frequency to daily; 6. Discuss with IEC and Contractor on remedial actions required; 7. If exceedance continues, arrange meeting with IEC and ER; 8. If exceedance stops, cease additional monitoring.	Check monitoring data submitted by ET; Check Contractor's working method; Discuss with ET and Contractor on possible remedial measures; Advise the ET on the effectiveness of the proposed remedial measures; Supervise Implementation of remedial measures.	Confirm receipt of notification of failure in writing; Notify Contractor; Ensure remedial measures properly implemented.	Submit proposals for remedial to ER within 3 working days of notification; Implement the agreed proposals; Amend proposal if appropriate.
Limit level exceedance for one sample	 Identify source, investigate the causes of exceedance and propose remedial measures; Inform ER, Contractor and EPD; Repeat measurement to confirm finding; Increase monitoring frequency to daily; Assess effectiveness of Contractor's remedial actions and keep IEC, EPD and ER informed of the results. 	 Check monitoring data submitted by ET; Check Contractor's working method; Discuss with ET and Contractor on possible remedial measures; Advise the ER on the effectiveness of the proposed remedial measures; Supervise implementation of remedial measures. 	Confirm receipt of notification of failure in writing; Notify Contractor; Ensure remedial measures properly implemented.	 Take immediate action to avoid further exceedance; Submit proposals for remedial actions to IEC within 3 working days of notification; Implement the agreed proposals; Amend proposal if appropriate.
Limit level exceedance for two or more consecutive samples	1. Notify IEC, ER, Contractor and EPD; 2. Identify source; 3. Repeat measurement to confirm findings; 4. Increase monitoring frequency to daily; 5. Carry out analysis of Contractor's working procedures to determine possible mitigation to be implemented; 6. Arrange meeting with IEC and ER to discuss the remedial actions to be taken; 7. Assess effectiveness of Contractor's remedial actions and keep IEC, EPD and ER informed of the results; 8. If exceedance stops, cease additional monitoring.	Discuss amongst ER, ET, and Contractor on the potential remedial actions; Review Contractor's remedial actions whenever necessary to assure their effectiveness and advise the ER accordingly; Supervise the implementation of remedial measures.	1. Confirm receipt of notification of failure in writing; 2. Notify Contractor; 3. In consultation with the IEC, agree with the Contractor on the remedial measures to be implemented; 4. Ensure remedial measures properly implemented; 5. If exceedance continues, consider what portion of the work is responsible and instruct the Contractor to stop that portion of work until the exceedance is abated.	Take immediate action to avoid further exceedance; Submit proposals for remedial actions to IEC within 3 working days of notification; Implement the agreed proposals; Resubmit proposals if problem still not under control; Stop the relevant portion of works as determined by the ER until the exceedance is abated.

 $Note: \quad ET-Environmental\ Team \qquad IEC-Independent\ Environmental\ Checker \qquad ER-Engineer's\ Representative$



Event and Action Plan for Construction Noise

Event		Acti		
Event	ET	IEC	ER	Contractor
Action Level	1. Notify IEC, ER and Contractor;	1. Review the analyzed results	1. Confirm receipt of notification of	1. Submit noise mitigation proposals to
Exceedance	2. Carry out investigation;	submitted by the ET;	failure in writing;	IEC and ER;
	3. Report the results of investigation to	2. Review the proposed remedial		2. Implement noise mitigation proposals
	the IEC, ER and Contractor;	measures by the Contractor and	1 1	
	4. Discuss with the Contractor and	advise the ER accordingly;	remedial measures for the analyzed	
	formulate remedial measures;	3. Supervise the implementation of	noise problem;	
	5. Increase monitoring frequency to	remedial measures.	4. Ensure remedial measures are	
	check mitigation effectiveness		properly implemented	
Limit Level	1. Identify source;	1. Discuss amongst ER, ET, and		1. Take immediate action to avoid
Exceedance	2. Inform IEC, ER, EPD and Contractor;	Contractor on the potential remedial	failure in writing;	further exceedance;
	3. Repeat measurements to confirm	actions;	2. Notify Contractor;	2. Submit proposals for remedial actions
	findings;	2. Review Contractors remedial actions	1 1	to IEC within 3 working days of
	4. Increase monitoring frequency;	whenever necessary to assure their		notification;
	5. Carry out analysis of Contractor's		noise problem;	3. Implement the agreed proposals;
	working procedures to determine	accordingly;	4. Ensure remedial measures properly	4. Resubmit proposals if problem still
	possible mitigation to be	3. Supervise the implementation of		not under control;
	implemented;	remedial measures.	5. If exceedance continues, consider	1 1
	6. Inform IEC, ER and EPD the causes		what portion of the work is	determined by the ER until the
	and actions taken for the		responsible and instruct the	exceedance is abated.
	exceedances;		Contractor to stop that portion of	
	7. Assess effectiveness of Contractor's		work until the exceedance is abated.	
	remedial actions and keep IEC, EPD			
	and ER informed of the results;			
	8. If exceedance stops, cease additional			
	monitoring.			

Note:

ET – Environmental Team

IEC – Independent Environmental Checker

ER – Engineer's Representative



Event and Action Plan for Water Quality

Event			Action	ion		
Event	ET	IEC	ER	Contractor		
Action level exceedance for one sampling day	Inform IEC, Contractor and ER; Check monitoring data, all plant, equipment and Contractor's working methods; and Discuss remedial measures with IEC and Contractor and ER.	Discuss with ET, ER and Contractor on the implemented mitigation measures; Review proposals on remedial measures submitted by Contractor and advise the ER accordingly; and Review and advise the ET and ER on the effectiveness of the implemented mitigation measures.	Discuss with IEC, ET and Contractor on the implemented mitigation measures; Make agreement on the remedial measures to be implemented; Supervise the implementation of agreed remedial measures.	I. Identify source(s) of impact; Inform the ER and confirm notification of the non-compliance in writing; Rectify unacceptable practice; Check all plant and equipment; Consider changes of working methods; Discuss with ER, ET and IEC and purpose remedial measures to IEC and ER; and Implement the agreed mitigation measures.		
Action level exceedance for more than one consecutive sampling days	Repeat in-situ measurement on next day of exceedance to confirm findings; Inform IEC, contractor and ER; Check monitoring data, all plant, equipment and Contractor's working methods; Discuss remedial measures with IEC, contractor and ER Ensure remedial measures are implemented	Discuss with ET, Contractor and ER on the implemented mitigation measures; Review the proposed remedial measures submitted by Contractor and advise the ER accordingly; and Review and advise the ET and ER on the effectiveness of the implemented mitigation measures.	Discuss with ET, IEC and Contractor on the proposed mitigation measures; Make agreement on the remedial measures to be implemented; and Discuss with ET, IEC and Contractor on the effectiveness of the implemented remedial measures.	I. Identify source(s) of impact; Inform the ER and confirm notification of the non-compliance in writing; Rectify unacceptable practice; Check all plant and equipment and consider changes of working methods; Discuss with ET, IEC and ER and submit proposal of remedial measures to ER and IEC within 3 working days of notification; and Implement the agreed mitigation measures.		
Limit level exceedance for one sampling day	Repeat measurement on next day of exceedance to confirm findings; Inform IEC, contractor and ER; Rectify unacceptable practice; Check monitoring data, all plant, equipment and Contractor's working methods; Consider changes of working methods; Discuss mitigation measures with IEC, ER and Contractor; and Ensure the agreed remedial measures are implemented	Discuss with ET, Contractor and ER on the implemented mitigation measures; Review the proposed remedial measures submitted by Contractor and advise the ER accordingly; and Review and advise the ET and ER on the effectiveness of the implemented mitigation measures.	Discuss with ET, IEC and Contractor on the implemented remedial measures; Request Contractor to critically review the working methods; Make agreement on the remedial measures to be implemented; and Discuss with ET, IEC and Contractor on the effectiveness of the implemented remedial measures.	Indentify source(s) of impact; Inform the ER and confirm notification of the non-compliance in writing; Rectify unacceptable practice; Check all plant and equipment and consider changes of working methods; Discuss with ET, IEC and ER and submit proposal of additional mitigation measures to ER and IEC within 3 working days of notification; and Implement the agreed remedial measures.		
Limit level exceedance for more than one consecutive sampling days	Inform IEC, contractor and ER; Check monitoring data, all plant, equipment and Contractor's working methods; Discuss mitigation measures with IEC, ER and Contractor; Ensure mitigation measures are implemented; and Increase the monitoring frequency to daily until no exceedance of Limit Level for two consecutive days	Discuss with ET, Contractor and ER on the implemented mitigation measures; Review the proposed remedial measures submitted by Contractor and advise the ER accordingly; and Review and advise the ET and ER on the effectiveness of the implemented mitigation measures.	Discuss with ET, IEC and Contractor on the implemented remedial measures; Request Contractor to critically review the working methods; Make agreement on the remedial measures to be implemented; Discuss with ET and IEC on the effectiveness of the implemented mitigation measures; and Consider and instruct, if necessary, the Contractor to slow down or to stop all or part of the construction activities until no exceedance of Limit level.	I. Identify source(s) of impact; Inform the ER and confirm notification of the non-compliance in writing; Rectify unacceptable practice; Check all plant and equipment and consider changes of working methods; Discuss with ET, IEC and ER and submit proposal of additional mitigation measures to ER and IEC within 3 working days of notification; and Implement the agreed remedial measures; and As directed by the ER, to slow down or stop all or part of the construction activities until no exceedance of Limit level.		

Note: ET – Environmental Team IEC – Independent Environmental Checker ER – Engineer's Representative Each step of actions required shall be implemented within 1 working day unless otherwise specified or agreed with EPD.



Appendix G

Monitoring Schedules of the Reporting Month and Coming Month



Monitoring Schedule of Air Quality, Noise and Water Quality in the Reporting Month - October 2018

	Date	Noise	Air Quality	Monitoring	Water Quality
	Date	Monitoring	1-Hour TSP	24-Hour TSP	vvace Quarty
Mon	1-Oct-18				
Tue	2-Oct-18			✓	✓
Wed	3-Oct-18	✓	✓		
Thu	4-Oct-18				✓
Fri	5-Oct-18				
Sat	6-Oct-18				✓
Sun	7-Oct-18				
Mon	8-Oct-18			✓	
Tue	9-Oct-18	✓	✓		✓
Wed	10-Oct-18				
Thu	11-Oct-18				✓
Fri	12-Oct-18				
Sat	13-Oct-18			✓	✓
Sun	14-Oct-18				
Mon	15-Oct-18	✓	✓		
Tue	16-Oct-18				✓
Wed	17-Oct-18				
Thu	18-Oct-18				✓
Fri	19-Oct-18			✓	
Sat	20-Oct-18		✓		✓
Sun	21-Oct-18				
Mon	22-Oct-18				
Tue	23-Oct-18				✓
Wed	24-Oct-18				
Thu	25-Oct-18			✓	✓
Fri	26-Oct-18	✓	✓		
Sat	27-Oct-18				✓
Sun	28-Oct-18				
Mon	29-Oct-18				✓
Tue	30-Oct-18				
Wed	31-Oct-18			✓	✓

✓	Monitoring Day
	Sunday or Public Holiday

Air Quality and Noise Monitoring Location

Environmental Aspect	Monitoring Location	Location
Air Quality	ASR-1	Sha Ling Village House No.6
Construction Noise	CN-1	Village house to the west of Sha Ling Road
Water Quality	M3	Wetland in the Conservation Area (CA) near Yuen Leng Chai



Monitoring Schedule of Air Quality, Noise and Water Quality in the next Month - November 2018

	Date	Noise Monitoring	Air Quality	y Monitoring	Water Quality
	Date	Noise Monitoring	1-Hour TSP	24-Hour TSP	, and Quarty
Thu	1-Nov-18	✓	✓		
Fri	2-Nov-18				✓
Sat	3-Nov-18				
Sun	4-Nov-18				
Mon	5-Nov-18				✓
Tue	6-Nov-18			✓	
Wed	7-Nov-18	✓	✓		✓
Thu	8-Nov-18				
Fri	9-Nov-18				✓
Sat	10-Nov-18				
Sun	11-Nov-18				
Mon	12-Nov-18			✓	✓
Tue	13-Nov-18	✓	✓		
Wed	14-Nov-18				✓
Thu	15-Nov-18				
Fri	16-Nov-18				✓
Sat	17-Nov-18			✓	
Sun	18-Nov-18				
Mon	19-Nov-18	✓	✓		✓
Tue	20-Nov-18				
Wed	21-Nov-18				✓
Thu	22-Nov-18				
Fri	23-Nov-18			✓	✓
Sat	24-Nov-18		✓		
Sun	25-Nov-18				
Mon	26-Nov-18				
Tue	27-Nov-18				✓
Wed	28-Nov-18				
Thu	29-Nov-18			✓	✓
Fri	30-Nov-18	✓	✓		

Remark: Impact monitoring for CV/2017/02 will be commenced on 5 November 2018.

✓	Monitoring Day
	Sunday or Public Holiday

Environmental Aspect	Location ID	Description of Location	Related Contract				
Construction	CN-1	Village house to the west of Sha Ling Road	CV/2016/10				
Noise	CN-3	San Uk Ling Village House No. 18	CV/2017/02				
Noise	CN-4	Muk Wu Village House No. 267	C V / 201 / / 02				
	ASR-1	Sha Ling Village House No. 6	CV/2016/10				
Air Quality	ASR-2	San Uk Ling Village House No.1	CV/2017/02				
	ASR-3	ASR-3 Muk Wu Nga Yiu House No.28					
	M3	Wetland in the Conservation Area near Yuen Leng Chai	CV/2016/10				
Water Ossalites	M1	Midstream of Nam Hang Stream					
Water Quality	M2	Downstream of Nam Hang Stream	CV/2017/02				
	M4	Watercourse across Lin Ma Hang Road					



Appendix H

Monitoring Data

- 24-Hour TSP Air Quality
- Noise
- Water Quality



Air Quality (24-hour TSP)



					24-	Hour	TSP N	Aonitor	ring Data	for ASR	·1				
DATE	SAMPLE NUMBER	EL	APSED TI	ME	СНА	RT REAI	DING	AVG TEMP	AVG AIR PRESS	STANDARD FLOW RATE	1 112	FILTER WEIGHT (g)		DUST WEIGHT COLLECTED	24-Hr TSP (μg/m³)
		INITIAL	FINAL	(min)	MIN	MAX	AVG	(℃)	(hPa)	(m³/min)	(std m ³)	INITIAL	FINAL	(g)	(, 0)
2-Oct-18	23147	8892.02	8915.54	1411.20	30	31	30.5	26.8	1012.3	1.15	1618	2.6614	2.8265	0.1651	102
8-Oct-18	23114	8915.54	8939.05	1410.60	30	31	30.5	26.3	1013	1.15	1618	2.6590	2.8144	0.1554	96
13-Oct-18	23062	8939.05	8962.55	1410.00	29	30	29.5	26.1	1013.8	1.12	1585	2.6888	2.8433	0.1545	97
19-Oct-18	23201	8962.55	8986.05	1410.00	31	33	32.0	24.2	1017.2	1.07	1510	2.6645	2.7774	0.1129	75
25-Oct-18	23238	8986.05	9009.55	1410.00	30	30	30.0	30.3	999.8	1.00	1408	2.6469	2.7758	0.1289	92
31-Oct-18	23220	9009.55	9033.08	1411.80	38	38	38.0	25	1014.2	1.24	1749	2.6393	2.8048	0.1655	95

CEDD No. Contract CV/2016/10 - Site Formation and Associated Infrastructural Works for Development of Columbarium at Sandy Ridge Cemetery Monthly Environmental Monitoring & Audit Report (No.3) – October 2018



Noise

CEDD No. Contract CV/2016/10 - Site Formation and Associated Infrastructural Works for Development of Columbarium at Sandy Ridge Cemetery

Monthly Environmental Monitoring & Audit Report (No.3) – October 2018



							Nois	e Mea	surer	nent]	Result	s (dB	(A)) c	of CN-	·1						
Date	Start Time	$\begin{array}{c} 1^{st} \\ Leq_{5min} \end{array}$	L10	L90	2 nd Leq _{5min}	L10	L90	3 nd Leq _{5min}	L10	L90	4 th Leq _{5min}	L10	L90	5 th Leq _{5min}	L10	L90	6 th Leq _{5min}	L10	L90	Leq _{30min}	Façade Collection
3-Oct-18	9:50	61.8	60.6	58.3	62.7	60.9	58.0	61.5	59.8	57.3	61.8	60.4	58.5	62.7	61.1	58.6	60.7	60.4	59.9	62	65
9-Oct-18	9:16	69.8	72.5	61.4	72.5	75.5	64.4	68.2	71.5	63.5	70.2	73.0	64.2	67.3	70.2	63.3	69.4	72.1	62.2	70	73
15-Oct-18	9:43	67.1	70.0	62.1	67.1	69.7	62.0	64.5	66.9	60.1	61.7	63.5	59.4	65.5	68.4	60.0	62.9	65.7	60.1	65	68
26-Oct-18	10:00	60.0	62.0	53.0	65.7	68.5	58.5	67.5	62.0	57.5	68.3	65.0	59.5	66.7	66.5	59.5	70.8	73.0	63.0	68	71



Water Quality



Water Quality Impact Monitoring at M3

																		2-Oct-18	Date
SS(mg/L)	SS	nity	Sali	H	p]	TU)	ity (NTU	Turbidi	(%)	DO	ng/L)	DO (Velocity (m/s)	Flow V	o (oC)	Temp	Depth (m)	Time	Location
6.0		0.0	0.0	7.6	7.58 7.58	0	8.0	8.07 7.95	59.4	59.1 59.7	4.8	4.74 4.78	0.1	0.1	26.7	26.7 26.7	2.50	9:50	M3
	Г						_			r		F						4-Oct-18	Date
SS(mg/L)		nity	Sali	H	p]	TU)	ity (NTU		(%)	DO	ng/L)		Velocity (m/s)		o (oC)	Temp	Depth (m)	Time	Location
8.5		0.0	0.0	7.4	7.38 7.38	5	5.5	5.42 5.55	61.8	61.8	4.9	4.92 4.92	0.1	0.1	27.0	27 27	2.50	9:45	M3
	-		-			-	·				.	_					·	6-Oct-18	Date
SS(mg/L)	SS	nity	Sali	H	pl	TU)	ity (NTU		(%)	DO	ng/L)		Velocity (m/s)	Flow V	o (oC)	Temp	Depth (m)	Time	Location
5 6.5		0.0	0.0	6.7	6.69	6	5.6	5.53 5.63	66.4	66.1 66.7	5.2	5.19 5.25	0.1	0.1	24.9	24.9 24.9	2.50	9:45	M3
							•	-		-		-		-					
·	•		-	•	•	-	•	-		-	•	_					-	9-Oct-18	Date
SS(mg/L)	SS	Salinity		pН		Turbidity (NTU)		DO (%)		DO (mg/L)		Velocity (m/s)	o (oC)	Temp	Depth (m)	Time	Location		
9 9.0	-	0.0	0.0	7.3	7.25 7.25	6	5.6	5.23 5.93	55.7	55.6 55.8	4.6	4.64	0.1	0.1	27.1	27.1 27.1	2.50	10:05	M3
					-			_				_					-		
												_						11-Oct-18	Date
SS(mg/L)		nity	Sali	H	p]	TU)	ity (NTU		(%)	DO	mg/L)		Velocity (m/s)		o (oC)	Temp	Depth (m)	Time	Location
7.0		0.0	0.0	6.7	5.23 8.23	8	7.8	7.49 8.08	53.8	53.8 53.8	4.6	4.63	0.2	0.2	24.5	24.5 24.5	2.50	10:00	M3
			-	-		-	-	-										13-Oct-18	Date
SS(mg/L)	SS	nitv	Sali	H	p]	TU)	ity (NTU	Turbidi	(%)	DO	mg/L)	DO (Velocity (m/s)	Flow V	(oC)	Temp	Depth (m)	Time	Location
6 6.0	6	0.0	0.0	7.3	7.33 7.33		5.3	5.20	67.3	69.1 65.5	5.4	5.54 5.25	0.1	0.1	24.2	24.2 24.2	2.50	10:00	M3
1				1			1	2.20			ı		1		1	_			
<u> </u>	•		-	•	•	-		-		-							-	16-Oct-18	Date
SS(mg/L)	Salinity		pН		Turbidity (NTU)			(%)	DO	mg/L)	DO (Velocity (m/s)	Flow V	o (oC)	Temp	Depth (m)	Time	Location	
3 3.0	3	0.0	0.0	8.5	8.48 8.48	0	4.0	4.00	69.1	69.0 69.2	5.7	5.65 5.67	0.1	0.1	25.5	25.5 25.5	2.50	11:00	M3
		•	0.0		8.48			4.00		69.0		5.65		0.1		25.5	1 1	Time	Location



Date	18-Oct-18																	
Location	Time	Depth (m)	Temp	o (oC)	Flow V	velocity (m/s)	DO (ı	mg/L)	DO	(%)	Turbidi	ty (NTU)	p]	H	Sali	nity	SS(1	ng/L)
M3	10:30	2.50	24	24.0	0.2	0.2	5.3	5.3	62.9	63.0	5.43	5.5	7.42	7.4	0.0	0.0	5	5.0
1713	10.50	2.30	24	24.0	0.2	0.2	5.31	3.3	63.1	03.0	5.55	3.3	7.42	7.4	0.0	0.0	5	3.0
	•	<u>-</u>							_	_	-							
Date	20-Oct-18	1									T							
Location	Time	Depth (m)	Temp	o (oC)		elocity (m/s)	DO (1	mg/L)		DO (%)		Turbidity (NTU)		H	Salinity		SS(mg/L)	
M3	9:40	2.50	24.5 24.5	24.5	0.1	0.1	5.79 5.82	5.8	72.7 73.1	72.9	5.13	5.3	7.18 7.18	7.2	0.0	0.0	3	3.0
		_																
Date	23-Oct-18																	
Location	Time	Depth (m)	Temp	o (oC)		elocity (m/s)	DO (1	mg/L)	DO	(%)		ty (NTU)	p]	H	Sali	nity		mg/L)
M3	10:00	2.50	25.4	25.4	0.1	0.1	5.4	5.4	65.8	65.9	5.22	5.3	7.40	7.4	0.0	0.0	9	8.5
1110	10.00	2.00	25.4		0.1	V.1	5.4	0	65.9	00.9	5.39	0.5	7.40	,	0.0	0.0	8	0.0
Date	25-Oct-18	-	-						_				-		-			-
Location	Time	Depth (m)	Temp	o (oC)	Flow V	elocity (m/s)	DO (mg/L)		DO (%)		Turbidity (NTU)		pН		Salinity		SS(mg/L)	
M3	9:45	2.50	25.6	25.6	0.1	0.1	5.09	5.1	62.2	62.4	7.54	7.9	8.66	8.7	0.0	0.0	11	11.5
1013	7.43	2.30	25.6	23.0	0.1	0.1	5.11	3.1	62.5	02.4	8.31	1.9	8.66	0.7	0.0	0.0	12	11.5
											.							
Date	27-Oct-18	1			T	1			1		т	-			T	-		
Location	Time	Depth (m)	Temp	o (oC)		relocity (m/s)	DO (1	mg/L)	DO	(%)		ty (NTU)	p.	H	Sali	nity	SS(mg/L)	
M3	9:55	2.50	25.5	25.5	0.1	0.1	5.97	6.0	76.8	76.9	4.16	4.4	7.68	7.7	0.0	0.0	8	8.0
			25.5		0.1		5.99		77.0		4.6		7.68	-	0.0		8	
Date	29-Oct-18																	
Location	Time	Depth (m)	Temp	(oC)	Flow V	elocity (m/s)	DO (ı	mg/L)	DO	(%)	Turbidi	ty (NTU)	p]	Ħ	Sali	nity	SSO	mg/L)
		• ` ` ′	24.2		0.1		5.49		65.5		4.88		7.74		0.0		6	
M3	10:05	2.50	24.2	24.2	0.1	0.1	5.5	5.5	65.6	65.6	4.9	4.9	7.74	7.7	0.0	0.0	3	4.5
		<u>.</u>							<u>.</u>									
Date	31-Oct-18		-															-
Location	Time	Depth (m)	Temp	o (oC)	Flow V	elocity (m/s)	DO (ı	mg/L)		DO (%)		Turbidity (NTU)		pН		Salinity		mg/L)
M3	10:00	2.50	23	23.0	0.1	0.1	5.12	5.1	62.1	62.2	5.18	5.2	8.06 8.06	8.1	0.0	0.0	5 4	4.5
	<u> </u>	<u> </u>	1	l.	1													





Appendix I

Graphical Plots of Air Quality, Noise and Water Quality




Air Quality Impact Monitoring









Construction Noise Impact Monitoring






Water Quality Impact Monitoring









Appendix J

Meteorological Data of the Reporting Period (Ta Kwu Ling Station)



Date				Ta Kwu Ling Station				
		Weather	Total Rainfall (mm)	Mean Air Temp. (°C)	Wind Speed (km/h)	Mean Relative Humidity (%)	Wind Direction	
1-Oct-18	Mon	Mainly cloudy with a few showers and isolated thunderstorms.	32	26	12.7	93.0	SE	
2-Oct-18	Tue	Mainly cloudy with isolated showers	9.8	27.3	5.5	84	S/SE	
3-Oct-18	Wed	Hot with sunny periods	0.3	27.7	6.5	80.7	E/SE	
4-Oct-18	Thu	Mainly fine and hot,	0	28.9	6	77.2	W/SW	
5-Oct-18	Fri	Very hot. Sunny periods with isolated showers and thunderstorms.	0.1	30	12.3	77.7	S/SW	
6-Oct-18	Sat	Very hot with sunny periods and a few showers.	0	29.3	6.8	81.2	E/NE	
7-Oct-18	Sun	Hot with sunny periods.	Trace	29.6	7.5	79.2	E/SE	
8-Oct-18	Mon	Very hot with sunny periods and a few showers.	24.6	27.7	16.1	81.0	N	
9-Oct-18	Tue	Mainly cloudy. Sunny intervals and isolated showers	16.7	27.2	6	73.7	E/NE	
10-Oct-18	Wed	Sunny periods. Isolated showers in the afternoon. Moderate easterly winds.	0.2	26	5.6	78.7	E/NE	
11-Oct-18	Thu	Mainly fine but hazy. Hot during the day. Moderate northerly winds.	0	27.4	6.5	68.7	N/NW	
12-Oct-18	Fri	Mainly cloudy with a few squally showers. Showers will be more frequent with thunderstorms	Trace	28.8	9.5	73	E/NE	
13-Oct-18	Sat	Mainly cloudy with showers. Isolated squally thunderstorms	167.5	28.5	8.4	78.7	E/NE	
14-Oct-18	Sun	Mainly cloudy with showers. Isolated squally thunderstorms at first.	0	29.5	6	75.7	N/NW	
15-Oct-18	Mon	Mainly fine but hazy. Hot during the day. Moderate northerly winds.	Trace	30	11	50.5	N	
16-Oct-18	Tue	occasionally strong on high ground	167.5	27.8	37	90	E/SE	
17-Oct-18	Wed	Mainly fine. Moderate to fresh east to southeasterly winds	12	28.5	17.2	78.5	E/SE	
18-Oct-18	Thu	Mainly fine. Moderate to fresh east to southeasterly winds	1.2	28.6	11	77.5	Е	
19-Oct-18	Fri	Fine and hot. Light winds.	0	28.4	5.5	76	SW	
20-Oct-18	Sat	Sunny periods. Isolated showers later. Light winds.	0	29.4	4.7	75.7	S/SW	
21-Oct-18	Sun	Fine. Very hot in the afternoon. Light winds.	Trace	29.4	5.5	70.7	S/SW	
22-Oct-18	Mon	Fine and hot. Light winds.	0	29.7	8.3	76.0	Е	
23-Oct-18	Tue	Sunny periods. Isolated showers later. Light winds.	Trace	29.5	9.6	74.7	E/SE	
24-Oct-18	Wed	Mainly cloudy with occasional showers and thunderstorms.	72.2	27.4	9.7	83.2	E/SE	
25-Oct-18	Thu	Mainly cloudy with one or two showers. Sunny periods tomorrow.	34.5	27.8	6.5	75	E/SE	
26-Oct-18	Fri	Mainly cloudy with one or two showers. Sunny periods tomorrow.	9.7	26.5	4.5	82	S/SW	
27-Oct-18	Sat	Fine and hot. Light winds.	Trace	Maintenanc e	5	Maintenanc e	Е	
28-Oct-18	Sun	Mainly fine. Dry in the afternoon. Moderate northerly winds.	0	26.7	9	76.5	N	
29-Oct-18	Mon	Fine. Very hot in the afternoon. Light winds.	0	27.4	25.2	60.0	N	
30-Oct-18	Tue	Mainly fine and dry. Moderate east to northeasterly winds.	0	27	22.9	60.0	N	
31-Oct-18	Wed	Very dry with sunny periods in the afternoon.	0	23.9	14.3	35.7	N/NE	



Appendix K

Ecology Survey Report



Contract No. CV/2016/10

Site Formation and Associated Infrastructural Works for Development of Columbarium, Crematorium and Related Facilities at Sandy Ridge Cemetery

Monthly Report of Ecologically Sensitive Habitats Monitoring – Oct 2018

Revision Date of issue	0 24 Oct 2018	
Prepared by	Alan Lam	未
Reviewed by	Edwina Yeung	(Fire)
Verified by	Desmond Tang	

1



Table of Contents

1	INT	RODUCTION	4
	1.1	BACKGROUND	4
	1.2	OBJECTIVE	4
2	ECC	DLOGICALLY SENSITIVE HABITATS	5
	2.1	DESCRIPTION OF HABITATS	5
	2.2	MONITORING MEASURES OF WETLAND HABITATS	6
	2.3	MONITORING MEASURES OF NON-WETLAND HABITATS	6
3	ME	THODOLOGY	7
	3.1	MAMMAL SURVEY	7
	3.2	BIRD SURVEY	7
	3.3	HERPETOFAUNA SURVEY	7
	3.4	DRAGONFLY SURVEY	7
	3.5	BUTTERFLY SURVEY	8
	3.6	AQUATIC FAUNA SURVEY	8
4	RES	ULT	9
Anr	endix l	– Transect Routes at Sandy Ridge	14



LIST OF TABLE	
Table 1	Action and Limit Levels and Responses to Evidence of Declines
	in Aquatic Fauna
Table 2	Action and Limit Levels and Responses to Evidence of Declines
	in Non-Aquatic Fauna
Table 3	Survey Schedule
Table 4	Result of Avifauna in survey
Table 5	Result of reptile in survey
Table 6	Result of amphibian in survey
Table 7	Result of butterfly in survey
Table 8	Result of Odonate in survey
Table 9	Result of freshwater communities in survey

LIST OF APPENI	<u>DIX</u>
Appendix I	Transect Routes at Sandy Ridge



1 INTRODUCTION

1.1 BACKGROUND

- 1.1.1 The main objective of the proposed site formation and associated infrastructural works for development of columbarium, crematorium (C&C) and related facilities at Sandy Ridge Cemetery is to increase the public cremation services and supply of public niches to meet the future demand.
- 1.1.2 The project includes site formation and associated works for development of C&C facilities at the Sandy Ridge Cemetery, road works within Sandy Ridge Cemetery, widening a section of Lin Ma Hang Road (from 6.5m to 7.3m), provision of off-site pick-up/drop-off points for shuttle buses as well as barging point at Siu Lam, Lok On Pai.
- 1.1.3 The Environmental Impact Assessment (EIA) report, including Environmental Monitoring and Audit Manual (EM&A Manual), was approved with conditions on 8 August 2016 (Register No.: AEIAR-198/2016). EPD issued an Environmental Permit (EP) for the Project (EP-487/2014) on 7 April 2017. A Further Environment Permit (FEP) for the Project (FEP-01/534/2017) was issued on 23 February 2018.
- 1.1.4 According to Clause 3.1 of the FEP (FEP-01/534/2017), "The Permit Holder shall implement the EM&A programme in accordance with the procedures and requirements as set out in the EM&A Manual. Any changes to the programme shall be justified by the ET Leader and verified by the IEC as conforming to the information and requirements contained in the EM&A Manual before submission to the Director for approval".
- 1.1.5 This Ecologically Sensitive Habitats Monitoring Methodology articulates the protocol of monitoring the ecology of concerned habitats as specified in EM&A Manual.

1.2 **OBJECTIVE**

- 1.2.1 According to approved EIA report (AEIAR-198/2016), habitat types within project boundary comprise of watercourse, grassland, upland grassland, plantation, woodland and developed area. Natural habitats were of moderate ecological value in terms of species diversity, species rarity, species abundance, ecological linkage as well as nursery. Moreover, 0.3ha of wet woodland on the northern side of Sandy Ridge was deemed habitat with high ecological value. Four types of habitats were regarded as ecologically sensitive habitats, namely wet woodland, watercourses, upland grassland and woodland. Considering human disturbance in upcoming construction and operation phases, ecologically sensitive habitats shall be monitored in accordance with EM&A Manual.
- 1.2.2 The objective of ecologically sensitive habitats monitoring is to evaluate the effectiveness of measures to minimize impacts on concerned habitats from disturbance and pollution.



2 ECOLOGICALLY SENSITIVE HABITATS

2.1 DESCRIPTION OF HABITATS

2.1.1 In order to monitor the effectiveness of the measures to the minimise impact on ecologically sensitive habitats from disturbance and pollution, monthly monitoring during construction and operation phases is required as specified in EM&A Manual. Standard faunal transect and sampling surveys cover both wetland and non-wetland habitats:

Wetland habitats	Non-wetland habitats
Wet Woodland	Upland Grassland
Watercourses	Woodland

- 2.1.2 Wet woodland is small patch present on northwest of the project boundary, and is confined by the marsh area to the north and the secondary woodland to the east, south and south-west parts. A number of mature trees Cleistocalyx nervosum and Acronychia pedunculata form the tree canopy, with other self-sown shrubs (including Psychotria asiatica, Ligustrum sinense and Glochidion lanceolarium) and trees (Aporosa dioica and Litsea monopetala). Whilst botanically it comprises of naturally regenerated secondary woodland and ground level are a series of small braided streams and weep points which even during the dry season remain wet. This creates a rather uncommon habitat in Hong Kong offering suitable conditions for a good assemblage of common wetland species. The wet woodland provides a good assemblage of micro-habitats, which is relatively undisturbed and has good linkages to other natural habitats. Several species of conversation importance were recorded in EIA report from this habitat: East Asian Porcupine, Leopard Cat, Red Muntjac, Two-striped Grass Frog, Small Snakehead, Somanniathelphusa zanklon, Dancing Shadow-emerald.
- 2.1.3 Seasonal watercourse running west to east in the eastern part of the area inside the Project boundary is shallower in gradient than those running off the hillside. This seasonal watercourse is heavily vegetated with wetland-associated herbs including *Commelina diffusa*, *Polygonum chinense*, *Colocasia esculenta* and *Dracaena sanderiana*. A mature tree of *Aquilaria sinensis* was recorded at the bank of the seasonal watercourse to the west of the Sandy Ridge Cemetery Office. Seasonal watercourses are restricted to the steeper slopes within the project boundary and are characterised by being entirely dry for much of the dry season. However, endemic crab *S. zanklon* population is supported by ephemeral watercourses close to the project boundary.
- 2.1.4 Upland grassland is the major habitat within the project boundary. The semi-natural habitat is dominated by typical upland grassland species: fern *Dicranopteris pedata*, grass *Neyraudia reynaudiana*, *Miscanthus floridulus*, climbing vines *Smilax china*, *Smilax glabra*, and shrubs such as *Rhodomyrtus tomentosa*, *Breynia fruticosa* and *Helicteres angustifolia*. Approximately 30 flowering spikes of two orchid species Bamboo Orchid and Toothed Habenaria were recorded near the hill top in the northern part of this upland grassland. Golden-headed Cisticola, which is considered as Local Concern by Fellowes *et al.* (2002), was also recorded in upland grassland on Sandy Ridge, including a proved breeding record of fledged young in September 2013. In addition, numerous species of conservation interest



were recorded in EIA report, such as East Asian Porcupine, Leopard Cat, Red Muntjac, Great Swift, Tamil Grass Dart, Small Three-ring and Small Grass Yellow.

2.1.5 Scattered patches of woodland are present throughout the assessment area, with the largest contiguous block located immediately to the east of the project boundary. These woodlands are relatively young with single-layered of canopy dominants (~10 – 15m tall) including *A. dioica*, *Bridelia tomentosa*, *Cinnamomum burmannii*, *Daphniphyllum calycinum*, *Litsea glutinosa*, *Rhus succedanea*, and *Zanthoxylum avicennae*. Such areas comprise secondary woodland which is largely derived from natural regeneration and colonisation of trees as a result of seed dispersal by birds and/or bats. A mature tree of *A. sinensis* is located at the woodland edge at the central part of the Project according to EIA report.

2.2 <u>MONITORING MEASURES OF WETLAND HABITATS</u>

- 2.2.1 Wetland habitats include wet woodland and watercourses. Monitoring surveys using standardised quantitative methodology will be conducted at fixed points. For seasonal watercourse, survey shall be conducted whenever the habitat appears.
- 2.2.2 Measures to respond to decreases in numbers of aquatic fauna using the wetland habitats and action and limit levels to trigger these measures are detailed in Table 1.

Action Level	Response	Limit Level	Response
Reduction in	Investigate cause and if	Reduction	Investigate cause and if
taxa diversity	cause identified as related	in taxa	cause identified as related
by 30%	to the project instigate	diversity	to the project instigate
	remedial action to remove	by 50%	remedial action.
	or reduce source of		
	disturbance.		

Table 1 Action and Limit Levels and Responses to Evidence of Declines in Aquatic Fauna

2.3 MONITORING MEASURES OF NON-WETLAND HABITATS

- 2.3.1 Non-wetland habitats consist of upland grassland and woodland. Monthly quantitative surveys of non-aquatic fauna will be conducted using standard route transect counts.
- 2.3.2 Measures to respond to decreases in numbers of non-aquatic fauna using the non-wetland habitats and action and limit levels to trigger these measures are detailed in Table 2.

Action Level	Response	Limit Level	Response
Reduction in	Investigate cause and if	Reduction	Investigate cause and if
species diversity	cause identified as related	in species	cause identified as related
by 30%	to the project instigate	diversity by	to the project instigate
	remedial action to remove	50%	remedial action.
	or reduce source of		
	disturbance.		

Table 2 Action and Limit Levels and Responses to Evidence of Declines in Non-Aquatic Fauna



3 METHODOLOGY

The ecological survey includes all taxa being investigated in EIA report. Table 3 summarizes schedule of faunal surveys.

Month	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Mammals	V	V	V									
Birds (day)	1	V	V	V	1	V	V	1	V	V	V	V
Birds (night)				V	√	√	1	√	V	V		
Herpetofau na				V	1	V	1	V	V	V		
Dragonflies			1	V	V	V	V	V	V	V		
Butterflies			1	V	V	V	V	V	V	V		
Aquatic fauna	√	√	1	V	V	V	1	V	V	√	V	V

Table 3 Survey Schedule

3.1 MAMMAL SURVEY

3.1.1 Mammal surveys will be conducted along the transects shown in Appendix 1 during both daytime and night time periods. Along with direct observations, other field signs, such as scats and tracks, will be searched and recorded if present.

3.2 BIRD SURVEY

3.2.1 Bird surveys will be conducted along the transects shown in Appendix 1 during the surveys, species and their vocalizing individuals recorded will be enumerated and recorded according to the habitat(s) they are utilising.

3.3 HERPETOFAUNA SURVEY

3.3.1 Reptile and amphibian surveys will be conducted along transects shown in Appendix 1 during surveys careful searches of appropriate microhabitats and refugia for reptiles and their vocalizing individuals will be undertaken and all reptiles observed will be identified and counted.

3.4 DRAGONFLY SURVEY

3.4.1 Dragonfly surveys will be conducted along transects shown in Appendix 1 during surveys all dragonflies seen will be identified and counted as accurately as possible.



3.5 BUTTERFLY SURVEY

3.5.1 Butterfly surveys will be conducted along transects shown in Appendix 1 during surveys all dragonflies seen will be identified and counted as accurately as possible.

3.6 AQUATIC FAUNA SURVEY

3.6.1 Freshwater fishes and macro-invertebrates will be recorded by direct observation. All species trapped/recorded will be enumerated and identified (to the lowest taxonomic level possible), and the species of conservation importance photographed.



4 RESULT

The 3rd monitoring survey started on 4th October 2018. The weather was fine. The survey included day and night sections, covering wetland and non-wetland areas. The survey was conducted by transect and fixed points. All species seen will be identified and counted as accurately as possible.

Mammal

There was no mammal recorded in the monitoring area.

■ Bird

There were a total of 32 bird individuals from 10 species recorded during the survey.

■ Herpetofauna

There were no reptile recorded in the monitoring area.

There were two amphibian (*Kaloula pulchra*, Asiatic Painted Frog, 花狹口蛙) and *Microhyla fissipes*, Ornate Pigmy Frog, 飾紋姬蛙) found in the monitoring area.

Dragonfly

There were a total of 13 odonate individuals from 2 species.

■ Butterfly

There were a total of 3 butterfly individuals from 3 species recorded.

■ Freshwater communities

2 crabs of conservation importance *Somanniathelphusa zanklon* (鐮刀束腰蟹) were found in marsh.










Table 4 Result of Avifauna in survey

Scientific Name	English Name	Chinese Name	Conservation Status	4-Oct-18		
Scientific Name	English Name	Chinese Name	Conservation Status	Non- wetland	Wetland	
Apus nipalensis	House Swift	小白腰雨燕		15		
Lanius schach	Long-tailed Shrike	棕背伯勞			1	
Dicrurus macrocercus	Black Drongo	黑卷尾		1		
Corvus macrorhynchos	Large-billed Crow	大嘴烏鴉		2		
Pycnonotus jocosus	Red-whiskered Bulbul	紅耳鵯		2		
Pycnonotus aurigaster	Sooty-headed Bulbul	白喉紅臀鵯		2		
Prinia inornata	Plain Prinia	純色鷦鶯			1	
Garrulax chinensis	Black-throated Laughingthrush	黑喉噪鶥			2	
Zosterops japonicus	Japanese White-eye	暗綠繡眼鳥		4		
Gracupica nigricollis	Black-collared Starling	黑領椋鳥			2	



Table 5 Result of reptile in survey

Scientific Name	Common Name	Chinese Name	4-Oct-18		
			Non-wetland	Wetland	
		N/A			

Table 6 Result of amphibian in survey

Scientific Name	Common Name	Chinese Name	Conservation	4-Oct-18	
			Status	Non- wetla nd	Wetland
Kaloula pulchra	Asiatic Painted Frog, Piebald Digging Frog	花狹口蛙			1
Microhyla fissipes	Ornate Pigmy Frog, Ornate Ricefrog, Ornamented Pygmy Frog	飾紋姬蛙		1	

Table 7 Result of butterfly in survey

Scientific Name	Common Name	Chinese Name	4-Oct-18			
			Non-wetland	Wetland		
Parnara guttata	Common Straight Swift	直紋稻弄蝶	1			
Rapala manea	Slate Flash	燕灰蝶	1			
Abisara echerius	Plum Judy	蛇目褐蜆蝶		1		




Table 8 Result of Odonate in survey

Scientific Name	Common Name	Chinese Name	Conservation Status	4-Oct-18	
				Non- wetland	Wetland
Ceriagrion auranticum	Orange-tailed Sprite	琉球橘黃蟌		1	
Pantala flavescens	Wandering Glider	黄蜻		12	

Table 9 Result of freshwater communities in survey

Scientific Name	Common Name	Chinese Name	Conservation Status	4-Oct-18
Somanniathelphusa zanklon		鐮刀束腰蟹	Fellowes et al. (2002): GC	2

Appendix I – Transect Routes at Sandy Ridge





Appendix L

Landscape & Visual Inspection Checklist



Contract No. CV/2016/10 Site Formation and Associated Infrastructural Works for Development of Columbarium, Crematorium

and Related Facilities at Sandy Ridge Cemetery Landscape and Visual Impact Assessment Checklist for Site Audit

Date: 29/10/2018 Weather: Fine/ Overcast/ Rain/ Windy

Item	Mitigation Measures	Implementation			Actions/ Remarks	
	7		No	N/A	7	
1	Landscape and Visual					
1.1	Is the construction period become shortened?			~	Under review.	
1.2	Is the work site confined within site boundaries and without encroaching into the landscape resources offsite?	~			Observation 1.	
1.3	Is the site kept clean and tidy (E.g. storage of materials, location and appearance of site accommodation being well positioned)	~			Observation 4 and 5	
1.4	Is the construction site screened properly by hoardings or noise barriers in visually unobstructed colours?	~			Observation 1.	
1.5	Is the erosion and dust control for exposed soil well performed during excavation work? (E.g. Exposed soil shall be covered or "camouflaged" and watered frequently. Areas that are expected to be left with bare soil for a long period of time should be hydro seeded and / or covered with suitable protective fabrics.)	,				
1.6	Are the woodland, plantation and other vegetation being protected and preserved in accordance with DEVB TC(W) No. 07/2015(E.g. Set up Tree Protection Zone)?	~			Observation 2, 3, 4 and 6	
1.7	Are the trees which are in direct conflict with the development proposal being transplanted as far as practical in accordance with and DEVB TC(W) No. 07/2015?	~				
1.8	Are compensatory planting for trees being provided to compensate the trees felled in accordance with DEVB TC(W) No. 07/2015?			~	Tree planting works have not yet been commenced.	
1.9	Are precautionary control measures to protect natural streams and rivers from adverse impact being implemented in accordance with ETWWB TCW No. 5/2005? (E.g. Construction debris and spoil should be covered up and properly disposed)	~				
1.10	Is light and glare control such as hooding being implemented during construction and operation to minimize light pollution and night time glare? (E.g. All security floodlights for construction sites should be equipped with adjustable shield, frosted diffusers and reflective covers)	,				



Summary / Remarks:

Follow up actions taken by Contractor for previous comments:

- 1. Trench Steel Sheet Piles were inserted in the earth bund. (Fig C)
- 2. Raised soil level to prevent muddy water enters the wet wood land. (Fig D)

The contractor was reminded to rectify the following: Outstanding observation from previous inspection

- 1. No hoarding and barrier was provided for demarcating the construction site. (Fig A)
- 2. No proper TPZ was provided for some of the retained trees. (Fig B)
- 3. Typhoon Mangkhut lead to fallen trees on site. (Fig E)


New Observation:

- 4. Construction material placing next to retained tree (Fig F)
- 5. Concrete leakage observed on the construction site (Fig G)
- 6. Raised soil level near root flare of tree (Fig H)


Reminders:

- 1. Construction works were being started. According to 'Tree Preservation' No7/2015, 26a, Contractor was reminded to provide TPZ with proper and robust fence at the dripline of all retained trees. No works were allowed to undertake within the TPZ.
- 2. Typhoon Mangkhut lead to fallen trees on site, contractor was reminded to remove these risk
- 3. Construction material was found placing next to the retained tree, the contractor is reminded to provide robust TPZ and do not place any construction material in it.
- 4. Concrete leakage on the construction site was observed, contractor is reminded to keep the site clean and tidy. Contractor reported that they will remove the concrete once they are solidified.
- 5. Raised soil level near root flare of tree was observed, as it may lead to suffocation of tree root, contractor is reminded to lower the soil level around the tree root flare.

Photo Record:



retained trees





Signature:

	Value Named	Signature alio	Date
Recorded by	Registered Landscape Architect	A Bull And	14/11/2018
Checked by	Environmental Team Leader	Am	14 November 2018
Checked by	Independent Environmental Checker	h	14 November 2018



Appendix M

Monthly Summary Waste Flow Table

Monthly Summary Waste Flow Table for October 2018

Department: Civil Engineering and Development Department Contract No.: CV/2016/10

Contract Title: Site Formation and Assoicated Infrastructural Works for Development of Columbarium at Sandy Ridge Cemetery

Commencement Date: 15-Dec-2017 Estimated completion Date 22-Dec-2023 Estimated Contract Sum: 780M

		Actual Quantities	s of Inert C&D M	laterials Generate	d Monthly			Actual Quantities	of C&D Wastes	Generated Monthl	d Monthly	
Month	Total Quantity Generated	Hard Rock and Large Broken Concrete	Reused in the Contract	Reused in other Projects	Disposed as Public Fill	Imported Fill	Metals	Paper/ cardboard packaging	Plastics (see Note 3)	Chemical Waste	Others, e.g. general refuse	
	(in '000m ³)	(in '000m ³)	(in '000m ³)	(in '000m ³)	(in '000m ³)	(in '000m ³)	(in '000 kg)	(in '000kg)	(in '000kg)	(in '000kg)	(in '000m ³)	
Jan	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.134	
Feb	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.127	
Mar	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.005	
Apr	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.071	
May	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.248	
June	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.019	
Sub-total	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.604	
July	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.064	
Aug	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	2.094	
Sept	22.980	0.000	0.991	0.000	21.989	0.000	0.000	0.000	0.000	0.000	0.075	
Oct	46.863	0.000	2.982	0.000	43.881	0.000	0.000	0.000	0.000	0.000	0.298	
Nov												
Dec												
Total	69.843	0.000	3.973	0.000	65.870	0.000	0.000	0.000	0.000	0.000	3.135	

Notes: (1) The waste flow table should cover the whole construction period of the Contract.

- (2) The original estimates of the C&D materials should be the estimates at contract commencement and should not be altered during construction.
- (3) Inert C&D materials that are specified in the Contract to be imported for use at the Site shall be separately indicated.
- (4) The yearly estimates of the C&D materials should be updated as appropriate taking into account the latest works programme etc.
- (5) Plastics refer to plastic bottles/containers, plastic sheets/foam from packaging material.
- (6) Broken concrete for recycling into aggregates.



Appendix N

Implementation Schedule for Environmental Mitigation Measures (ISEMM)

Environmental Mitigation Implementation Schedule – Sandy Ridge

EIA Ref.	Recommended Mitigation Measures	Objectives of the Recommended Measures & Main Concerns to address	Implementation Agent	Location / Timing	Implementation Stage	Requirements and / or standards to be achieved
EM&A Project						
S13.1.1.1, S13.2.1.2	An Independent Environmental Checker needs to be employed as per the EM&A Manual.	Control EM&A Performance	Highways Department	All construction sites	Construction phase	• EIAO Guidance Note No.4/2010 • TM-EIAO
S13.2.1.1 – S13.4.1.2	 An Environmental Team needs to be employed as per the EM&A Manual. Prepare a systematic Environmental Management Plan to ensure effective implementation of the mitigation measures. An environmental impact monitoring needs to be implementing by the Environmental Team to ensure all the requirements given in the EM&A Manual are fully complied with. 	Perform environmental monitoring & auditing	Highways Department / Contractor	All construction sites	Construction phase	• EIAO Guidance Note No.4/2010 • TM-EIAO